

日立照明器具 照明特性

形式: TLE45401D-JZU14 <高出力タイプ> <昼光色相当> <照度補正、連続調光共用形>	反射率	天井	80%			70%			50%			30%				
	壁	70%	50%	30%	70%	50%	30%	10%	50%	30%	10%	50%	30%	10%		
	床	10%												0%		
	室指数	照明率 S/H=1.0														
姿図	0.6	0.63	0.52	0.45	0.62	0.51	0.44	0.40	0.50	0.44	0.40	0.49	0.44	0.39	0.38	
	0.8	0.72	0.62	0.55	0.71	0.62	0.55	0.50	0.60	0.54	0.50	0.59	0.54	0.50	0.48	
	1	0.79	0.70	0.63	0.77	0.69	0.62	0.58	0.67	0.62	0.57	0.66	0.61	0.57	0.55	
	1.25	0.84	0.76	0.70	0.83	0.75	0.69	0.65	0.74	0.68	0.64	0.72	0.67	0.64	0.62	
	1.5	0.88	0.81	0.75	0.87	0.80	0.75	0.70	0.78	0.74	0.70	0.77	0.73	0.69	0.67	
	2	0.93	0.87	0.83	0.92	0.86	0.82	0.78	0.85	0.81	0.77	0.83	0.79	0.76	0.74	
	2.5	0.96	0.91	0.87	0.95	0.90	0.86	0.83	0.88	0.85	0.82	0.86	0.83	0.81	0.78	
	3	0.98	0.94	0.90	0.97	0.93	0.89	0.86	0.91	0.87	0.85	0.89	0.86	0.84	0.81	
光源	4	1.01	0.97	0.94	0.99	0.96	0.93	0.90	0.94	0.91	0.89	0.92	0.90	0.88	0.85	
品名	LED	5	1.02	1.00	0.97	1.01	0.98	0.96	0.94	0.96	0.94	0.92	0.94	0.92	0.91	0.88
形式		7	1.05	1.03	1.01	1.03	1.01	1.00	0.98	0.99	0.98	0.96	0.97	0.96	0.95	0.92
光束	11,340 lm	10	1.06	1.05	1.04	1.05	1.04	1.03	1.01	1.02	1.01	1.00	1.00	0.99	0.98	0.95
器具効率 Ft=	100.0%	単体照度分布(初期)														
上方光束 Fu=	0.0%	800 600 400 200														
下方光束 Fd=	100.0%	0.0 1.5 3.0														
配光分類	BZ-	3.0 1.5 0.0 1.5 3.0														
最大取付間隔	A-A 1.30 H	A B														
	B-B 1.18 H	配光曲線														
保守率	良 0.81	180 150 120 90 60 30 0														
	中 0.77	450.0 400.0 350.0 300.0 250.0 200.0 150.0 100.0 50.0 0.0														
	否 0.68	A B C-C'														
光度 (cd/1000 lm)	A-0 B-B C-0 A'-0 C'-0	0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150 160 170 180														
	438 438 438	430 427 428														
	408 390 394	381 342 351														
	308 280 300	184 217 214														
	85 137 116	44 70 50														
	18 22 20	100 110 120 130 140 150 160 170 180														