



日立照明器具 照明特性

名称: 直管形LED搭載器具	反射率	天井	80%			70%				50%			30%			0%																																																																																																																							
		壁	70%	50%	30%	70%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0%																																																																																																																							
		床	10%														0%																																																																																																																						
形式: TME4222-XM14E	室指数	照明率 S/H=1.0																																																																																																																																					
<備考>	0.6	0.49	0.38	0.31	0.48	0.38	0.31	0.27	0.37	0.31	0.26	0.36	0.30	0.26	0.25																																																																																																																								
	0.8	0.58	0.47	0.40	0.56	0.47	0.40	0.35	0.45	0.39	0.35	0.44	0.39	0.34	0.33																																																																																																																								
姿図 	1	0.64	0.54	0.47	0.62	0.53	0.46	0.41	0.51	0.45	0.41	0.50	0.45	0.40	0.38																																																																																																																								
	1.25	0.69	0.60	0.53	0.67	0.59	0.53	0.48	0.57	0.52	0.47	0.56	0.51	0.47	0.45																																																																																																																								
	1.5	0.73	0.65	0.58	0.71	0.64	0.58	0.53	0.62	0.57	0.52	0.60	0.56	0.52	0.50																																																																																																																								
	2	0.78	0.71	0.66	0.77	0.70	0.65	0.61	0.68	0.64	0.60	0.67	0.63	0.59	0.57																																																																																																																								
	2.5	0.81	0.75	0.70	0.80	0.74	0.70	0.66	0.72	0.68	0.65	0.71	0.67	0.64	0.62																																																																																																																								
	3	0.83	0.78	0.74	0.82	0.77	0.73	0.69	0.75	0.72	0.68	0.73	0.70	0.67	0.65																																																																																																																								
	4	0.86	0.82	0.78	0.85	0.81	0.78	0.75	0.79	0.76	0.73	0.77	0.75	0.72	0.70																																																																																																																								
光源	5	0.88	0.85	0.82	0.87	0.84	0.81	0.78	0.82	0.79	0.77	0.80	0.78	0.76	0.73																																																																																																																								
品名 直管形LEDランプ	7	0.90	0.88	0.86	0.89	0.87	0.85	0.83	0.85	0.83	0.81	0.83	0.81	0.80	0.77																																																																																																																								
形式 LDK40SS・D/15/23NE	10	0.92	0.90	0.89	0.91	0.89	0.88	0.86	0.87	0.86	0.85	0.85	0.84	0.83	0.81																																																																																																																								
光束 4,660 lm																																																																																																																																							
器具効率 Ft= 88.0%		単体照度分布(初期値) 																																																																																																																																					
上方光束 Fu= 0%																																																																																																																																							
下方光束 Fd= 88.0%																																																																																																																																							
最大取付間隔		配光曲線 																																																																																																																																					
A-A 1.34 H																																																																																																																																							
B-B 1.28 H																																																																																																																																							
保守率	良															0.86																																																																																																																							
	中															0.81																																																																																																																							
	否															0.72																																																																																																																							
光度 (cd/1000 lm)																<table><tr><th></th><th>A-0</th><th>B-B</th><th>C-0</th><th>A'-0</th><th>C'-0</th></tr><tr><td>0</td><td>268</td><td>268</td><td>268</td><td></td><td></td></tr><tr><td>10</td><td>264</td><td>264</td><td>264</td><td></td><td></td></tr><tr><td>20</td><td>255</td><td>252</td><td>253</td><td></td><td></td></tr><tr><td>30</td><td>239</td><td>230</td><td>235</td><td></td><td></td></tr><tr><td>40</td><td>220</td><td>201</td><td>209</td><td></td><td></td></tr><tr><td>50</td><td>201</td><td>167</td><td>185</td><td></td><td></td></tr><tr><td>60</td><td>168</td><td>125</td><td>154</td><td></td><td></td></tr><tr><td>70</td><td>114</td><td>76</td><td>112</td><td></td><td></td></tr><tr><td>80</td><td>42</td><td>34</td><td>54</td><td></td><td></td></tr><tr><td>90</td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>100</td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>110</td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>120</td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>130</td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>140</td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>150</td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>160</td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>170</td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>180</td><td></td><td></td><td></td><td></td><td></td></tr></table>															A-0	B-B	C-0	A'-0	C'-0	0	268	268	268			10	264	264	264			20	255	252	253			30	239	230	235			40	220	201	209			50	201	167	185			60	168	125	154			70	114	76	112			80	42	34	54			90						100						110						120						130						140						150						160			
	A-0	B-B	C-0	A'-0	C'-0																																																																																																																																		
0	268	268	268																																																																																																																																				
10	264	264	264																																																																																																																																				
20	255	252	253																																																																																																																																				
30	239	230	235																																																																																																																																				
40	220	201	209																																																																																																																																				
50	201	167	185																																																																																																																																				
60	168	125	154																																																																																																																																				
70	114	76	112																																																																																																																																				
80	42	34	54																																																																																																																																				
90																																																																																																																																							
100																																																																																																																																							
110																																																																																																																																							
120																																																																																																																																							
130																																																																																																																																							
140																																																																																																																																							
150																																																																																																																																							
160																																																																																																																																							
170																																																																																																																																							
180																																																																																																																																							