



日立照明器具 照明特性

名称: 一体形LEDベース (スクエアタイプ)	天井 反射率	80%			70%				50%			30%			0%	
		壁	70%	50%	30%	70%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0%
形式: TPE454AD-JZU14A	床 室指数	10%														0%
		固有照明率 S/H=1.0														
〈備考〉	0.6	0.59	0.47	0.39	0.57	0.46	0.39	0.34	0.45	0.38	0.34	0.44	0.38	0.33	0.32	
	0.8	0.68	0.57	0.49	0.67	0.56	0.49	0.44	0.55	0.48	0.43	0.54	0.48	0.43	0.41	
姿図 	1	0.75	0.64	0.57	0.73	0.63	0.56	0.51	0.62	0.55	0.50	0.60	0.55	0.50	0.48	
	1.25	0.81	0.71	0.64	0.79	0.70	0.63	0.58	0.68	0.62	0.58	0.67	0.61	0.57	0.55	
	1.5	0.85	0.76	0.70	0.83	0.75	0.69	0.64	0.74	0.68	0.64	0.72	0.67	0.63	0.61	
	2	0.91	0.83	0.78	0.89	0.82	0.77	0.72	0.80	0.76	0.72	0.78	0.74	0.71	0.68	
	2.5	0.94	0.88	0.83	0.92	0.87	0.82	0.78	0.85	0.80	0.77	0.83	0.79	0.76	0.73	
	3	0.96	0.91	0.86	0.95	0.90	0.85	0.82	0.87	0.84	0.80	0.85	0.82	0.79	0.77	
光源形式 -	4	0.99	0.95	0.91	0.98	0.94	0.90	0.87	0.91	0.88	0.86	0.89	0.87	0.84	0.82	
	5	1.01	0.98	0.94	1.00	0.96	0.93	0.91	0.94	0.92	0.89	0.92	0.90	0.88	0.85	
器具光束 9,480 lm	7	1.03	1.01	0.99	1.02	1.00	0.98	0.96	0.98	0.96	0.94	0.95	0.94	0.92	0.90	
	10	1.05	1.04	1.02	1.04	1.02	1.01	0.99	1.00	0.99	0.98	0.98	0.97	0.96	0.93	

器具効率 Ft= 100%					
上方光束 Fu= 0%					
下方光束 Fd= 100%					
最大取付間隔					
A-A		1.26 H			
B-B		1.26 H			
保守率	良	0.81			
	中	0.77			
	否	0.72			
光度 (cd/1000 lm)					
	A-0	B-B	C-0	A'-0	C'-0
0	357	357	357		
10	349	347	348		
20	329	329	330		
30	298	298	299		
40	259	258	255		
50	208	212	212		
60	159	156	153		
70	88	91	94		
80	37	37	38		
90					
100					
110					
120					
130					
140					
150					
160					
170					
180					

単体照度分布 (初期値)



800 600 400 200

3.0 1.5 0.0 1.5 3.0


0.0 1.5 3.0

A ← 水平距離(m) → B

(m) 高さ

0-200
200-400
400-600
600-800
800-1000

配光曲線
(cd/1000 lm)



180 150 120 90 60 30 0 30 60 90 120 150 180

400.0 350.0 300.0 250.0 200.0 150.0 100.0 50.0 0.0

A
B
C-C'