




日立照明器具 照明特性

名称: 高天井用LED器具	反射率	天井	80%			70%				50%			30%			0%																																																																																																																							
		壁	70%	50%	30%	70%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0%																																																																																																																							
		床	10%														0%																																																																																																																						
形式: WGMTE22ANN-J14A	室指数	固有照明率 S/H=1.0																																																																																																																																					
<備考> 配光角(中角)	0.6	0.74	0.66	0.61	0.73	0.66	0.61	0.57	0.65	0.60	0.57	0.64	0.60	0.57	0.55																																																																																																																								
	0.8	0.83	0.76	0.71	0.82	0.75	0.70	0.67	0.74	0.70	0.66	0.73	0.69	0.66	0.65																																																																																																																								
姿図 	1	0.88	0.81	0.77	0.87	0.81	0.76	0.73	0.80	0.76	0.73	0.79	0.75	0.72	0.71																																																																																																																								
	1.25	0.92	0.86	0.82	0.91	0.86	0.82	0.79	0.84	0.81	0.78	0.83	0.80	0.78	0.76																																																																																																																								
	1.5	0.95	0.90	0.86	0.94	0.89	0.86	0.83	0.88	0.85	0.82	0.87	0.84	0.82	0.80																																																																																																																								
	2	0.99	0.95	0.92	0.98	0.94	0.91	0.88	0.92	0.90	0.88	0.91	0.89	0.87	0.85																																																																																																																								
	2.5	1.01	0.97	0.94	1.00	0.96	0.94	0.91	0.95	0.92	0.90	0.93	0.91	0.89	0.87																																																																																																																								
	3	1.02	0.99	0.96	1.01	0.98	0.96	0.93	0.96	0.94	0.92	0.94	0.93	0.91	0.89																																																																																																																								
	4	1.03	1.01	0.99	1.02	1.00	0.98	0.96	0.98	0.97	0.95	0.96	0.95	0.94	0.91																																																																																																																								
光源形式	5	1.05	1.03	1.01	1.03	1.02	1.00	0.99	1.00	0.98	0.97	0.98	0.97	0.96	0.93																																																																																																																								
器具光束 19,700 lm	7	1.06	1.05	1.04	1.05	1.04	1.03	1.02	1.02	1.01	1.00	1.00	0.99	0.98	0.96																																																																																																																								
	10	1.07	1.07	1.06	1.06	1.06	1.05	1.04	1.04	1.03	1.02	1.02	1.01	1.01	0.98																																																																																																																								
器具効率 Ft= 100%		単体照度分布(初期値) 																																																																																																																																					
上方光束 Fu= 0%																																																																																																																																							
下方光束 Fd= 100%																																																																																																																																							
最大取付間隔		配光曲線 (cd/1000 lm) 																																																																																																																																					
A-A 0.90 H																																																																																																																																							
B-B 0.90 H																																																																																																																																							
保守率	良	0.81																																																																																																																																					
	中	0.79																																																																																																																																					
	否	0.75																																																																																																																																					
光度 (cd/1000 lm)		<table><tr><th></th><th>A-0</th><th>B-B</th><th>C-0</th><th>A'-0</th><th>C'-0</th></tr><tr><td>0</td><td>836</td><td>836</td><td>836</td><td></td><td></td></tr><tr><td>10</td><td>788</td><td>788</td><td>788</td><td></td><td></td></tr><tr><td>20</td><td>631</td><td>631</td><td>627</td><td></td><td></td></tr><tr><td>30</td><td>442</td><td>430</td><td>447</td><td></td><td></td></tr><tr><td>40</td><td>293</td><td>271</td><td>278</td><td></td><td></td></tr><tr><td>50</td><td>149</td><td>129</td><td>135</td><td></td><td></td></tr><tr><td>60</td><td>46</td><td>44</td><td>38</td><td></td><td></td></tr><tr><td>70</td><td>6</td><td>6</td><td>4</td><td></td><td></td></tr><tr><td>80</td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>90</td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>100</td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>110</td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>120</td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>130</td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>140</td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>150</td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>160</td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>170</td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>180</td><td></td><td></td><td></td><td></td><td></td></tr></table>															A-0	B-B	C-0	A'-0	C'-0	0	836	836	836			10	788	788	788			20	631	631	627			30	442	430	447			40	293	271	278			50	149	129	135			60	46	44	38			70	6	6	4			80						90						100						110						120						130						140						150						160						170						180					
	A-0	B-B	C-0	A'-0	C'-0																																																																																																																																		
0	836	836	836																																																																																																																																				
10	788	788	788																																																																																																																																				
20	631	631	627																																																																																																																																				
30	442	430	447																																																																																																																																				
40	293	271	278																																																																																																																																				
50	149	129	135																																																																																																																																				
60	46	44	38																																																																																																																																				
70	6	6	4																																																																																																																																				
80																																																																																																																																							
90																																																																																																																																							
100																																																																																																																																							
110																																																																																																																																							
120																																																																																																																																							
130																																																																																																																																							
140																																																																																																																																							
150																																																																																																																																							
160																																																																																																																																							
170																																																																																																																																							
180																																																																																																																																							