




日立照明器具 照明特性

名称: 高天井用LED器具	反射率	天井	80%			70%				50%			30%			0%
		壁	70%	50%	30%	70%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0%
		床	10%													
形式: WGMTE4401MN-J24A	室指数	固有照明率 S/H=1.0														
<備考>	0.6	0.64	0.53	0.46	0.63	0.53	0.46	0.41	0.52	0.46	0.41	0.51	0.45	0.41	0.39	
	0.8	0.74	0.64	0.57	0.72	0.63	0.57	0.52	0.62	0.56	0.52	0.61	0.56	0.52	0.50	
姿図 	1	0.80	0.71	0.65	0.79	0.71	0.65	0.60	0.69	0.64	0.60	0.68	0.63	0.59	0.57	
	1.25	0.86	0.78	0.72	0.84	0.77	0.72	0.67	0.75	0.71	0.67	0.74	0.70	0.66	0.64	
	1.5	0.90	0.83	0.77	0.88	0.82	0.77	0.73	0.80	0.76	0.72	0.79	0.75	0.72	0.70	
	2	0.95	0.89	0.85	0.93	0.88	0.84	0.80	0.86	0.83	0.80	0.85	0.82	0.79	0.77	
	2.5	0.97	0.93	0.89	0.96	0.92	0.88	0.85	0.90	0.87	0.84	0.88	0.85	0.83	0.81	
	3	0.99	0.95	0.91	0.98	0.94	0.91	0.88	0.92	0.89	0.87	0.90	0.88	0.86	0.83	
	4	1.02	0.98	0.95	1.00	0.97	0.94	0.92	0.95	0.93	0.91	0.93	0.91	0.89	0.87	
光源形式	5	1.03	1.00	0.98	1.02	0.99	0.97	0.95	0.97	0.95	0.94	0.95	0.94	0.92	0.90	
器具光束 43,000 lm	7	1.05	1.03	1.02	1.04	1.02	1.01	0.99	1.00	0.99	0.97	0.98	0.97	0.96	0.93	
	10	1.07	1.05	1.04	1.05	1.04	1.03	1.02	1.02	1.01	1.01	1.00	0.99	0.99	0.96	
器具効率 Ft= 100%		単体照度分布(初期値) 														
上方光束 Fu= 0%																
下方光束 Fd= 100%																
最大取付間隔																
A-A 1.36 H																
B-B H																
保守率	良	0.81														
	中	0.79														
	否	0.75														
光度 (cd/1000 lm)		配光曲線 (cd/1000 lm) 														
A-0	B-B															C-0
0	380															
10	401															
20	459															
30	363															
40	287															
50	225															
60	130															
70	26															
80	5															
90																
100																
110																
120																
130																
140																
150																
160																
170																
180																