

日立照明器具 照明特性

名称: 高天井用LED器具	反射率	天井	80%			70%				50%			30%			0%
		壁	70%	50%	30%	70%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0%
		床	10%													
形式: WGMTE44BNN-J24A	室指数	固有照明率 S/H=1.0														
<備考>	0.6	0.72	0.64	0.58	0.71	0.63	0.58	0.54	0.62	0.57	0.54	0.61	0.57	0.54	0.52	
	0.8	0.81	0.73	0.68	0.80	0.73	0.68	0.64	0.72	0.67	0.64	0.71	0.67	0.63	0.62	
姿図	1	0.86	0.79	0.74	0.85	0.79	0.74	0.70	0.77	0.73	0.70	0.76	0.73	0.70	0.68	
	1.25	0.91	0.85	0.80	0.90	0.84	0.80	0.76	0.82	0.79	0.76	0.81	0.78	0.75	0.73	
	1.5	0.94	0.88	0.84	0.93	0.88	0.84	0.81	0.86	0.83	0.80	0.85	0.82	0.79	0.78	
	2	0.98	0.93	0.90	0.97	0.93	0.89	0.87	0.91	0.88	0.86	0.89	0.87	0.85	0.83	
	2.5	1.00	0.96	0.93	0.99	0.95	0.92	0.90	0.93	0.91	0.89	0.92	0.90	0.88	0.86	
	3	1.01	0.98	0.95	1.00	0.97	0.94	0.92	0.95	0.93	0.91	0.93	0.91	0.90	0.88	
光源形式	4	1.03	1.00	0.98	1.02	0.99	0.97	0.95	0.97	0.95	0.94	0.95	0.94	0.93	0.90	
	5	1.04	1.02	1.00	1.03	1.01	0.99	0.98	0.99	0.97	0.96	0.97	0.96	0.95	0.92	
器具光束	7	1.06	1.04	1.03	1.04	1.03	1.02	1.01	1.01	1.00	0.99	0.99	0.98	0.98	0.95	
	40,250 lm	10	1.07	1.06	1.05	1.06	1.05	1.04	1.04	1.03	1.02	1.02	1.01	1.00	0.97	
器具効率 Ft= 100%		単体照度分布(初期値)														
上方光束 Fu= 0%		800 600 400 200														
下方光束 Fd= 100%		10.0 5.0 0.0 5.0 10.0														
		0.0 5.0 10.0														
最大取付間隔		(m) 単位														
A-A 1.00 H		0-200														
B-B 1.00 H		200-400														
保守率	良	0.83	400-600													
	中	0.81	600-800													
	否	0.76	800-1000													
光度 (cd/1000 lm)		A ← 水平距離(m) → B														
	A-0	B-B	C-0	A'-0	C'-0	配光曲線 (cd/1000 lm)										
0	753	753	753			180										
10	777	786	793			150										
20	636	630	621			120										
30	441	445	447			90										
40	280	283	282			60										
50	134	137	136			30										
60	40	41	37			0										
70	5	6	4			A										
80			2			B										
90						C-C'										
100																
110																
120																
130																
140																
150																
160																
170																
180																