




日立照明器具 照明特性

名称: 高天井用LED器具	反射率	天井	80%			70%				50%			30%			0%
		壁	70%	50%	30%	70%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0%
		床	10%													
形式: WHMTE1403MN-J14	室指数	固有照明率 S/H=1.0														
＜備考＞	0.6	0.66	0.55	0.49	0.65	0.55	0.48	0.44	0.54	0.48	0.44	0.53	0.48	0.44	0.42	
	0.8	0.76	0.66	0.60	0.74	0.66	0.60	0.55	0.64	0.59	0.55	0.63	0.58	0.55	0.53	
姿図 	1	0.82	0.74	0.67	0.81	0.73	0.67	0.63	0.71	0.66	0.62	0.70	0.66	0.62	0.60	
	1.25	0.87	0.80	0.74	0.86	0.79	0.74	0.70	0.78	0.73	0.69	0.76	0.72	0.69	0.67	
	1.5	0.91	0.85	0.80	0.90	0.84	0.79	0.75	0.82	0.78	0.75	0.81	0.77	0.74	0.72	
	2	0.96	0.91	0.87	0.95	0.90	0.86	0.83	0.88	0.85	0.82	0.86	0.84	0.81	0.79	
	2.5	0.99	0.94	0.90	0.97	0.93	0.90	0.87	0.91	0.88	0.86	0.90	0.87	0.85	0.83	
	3	1.00	0.96	0.93	0.99	0.95	0.92	0.90	0.93	0.91	0.88	0.92	0.89	0.87	0.85	
	4	1.02	0.99	0.97	1.01	0.98	0.96	0.93	0.96	0.94	0.92	0.94	0.93	0.91	0.88	
光源形式	5	1.04	1.01	0.99	1.03	1.00	0.98	0.96	0.98	0.97	0.95	0.96	0.95	0.93	0.91	
器具光束 13,090 lm	7	1.06	1.04	1.03	1.05	1.03	1.02	1.00	1.01	1.00	0.99	0.99	0.98	0.97	0.94	
	10	1.07	1.06	1.05	1.06	1.05	1.04	1.03	1.03	1.02	1.01	1.01	1.00	1.00	0.97	
器具効率 Ft= 100%		単体照度分布(初期値) 														
上方光束 Fu= 0%																
下方光束 Fd= 100%																
最大取付間隔		A-A 1.38 H B-B H														
保守率	良	0.81														
	中	0.79														
	否	0.75														
光度 (cd/1000 lm)		配光曲線 (cd/1000 lm) 														
	A-0	B-B	C-0	A'-0	C'-0											
0	387															
10	429															
20	493															
30	388															
40	301															
50	226															
60	104															
70	16															
80	1															
90																
100																
110																
120																
130																
140																
150																
160																
170																
180																