



日立照明器具 照明特性

名称: LEDダウンライト	反射率	天井	80%				70%				50%			30%			0%
		壁	70%	50%	30%	70%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0%	
		床	10%														0%
形式: WLDE4307WL	室指数	固有照明率 S/H=1.0															
〈備考〉	0.6	0.63	0.52	0.45	0.62	0.51	0.45	0.40	0.50	0.44	0.40	0.49	0.44	0.40	0.38		
	0.8	0.73	0.63	0.56	0.72	0.62	0.56	0.51	0.61	0.55	0.51	0.60	0.55	0.51	0.49		
姿図 	1	0.80	0.71	0.64	0.78	0.70	0.64	0.59	0.68	0.63	0.59	0.67	0.62	0.58	0.56		
	1.25	0.85	0.77	0.71	0.84	0.77	0.71	0.67	0.75	0.70	0.66	0.73	0.69	0.66	0.64		
	1.5	0.90	0.83	0.77	0.88	0.82	0.77	0.72	0.80	0.75	0.72	0.78	0.74	0.71	0.69		
	2	0.95	0.89	0.84	0.93	0.88	0.84	0.80	0.86	0.82	0.79	0.84	0.81	0.79	0.76		
	2.5	0.97	0.93	0.89	0.96	0.92	0.88	0.85	0.90	0.86	0.84	0.88	0.85	0.83	0.80		
	3	0.99	0.95	0.91	0.98	0.94	0.91	0.88	0.92	0.89	0.87	0.90	0.88	0.85	0.83		
	4	1.01	0.98	0.95	1.00	0.97	0.94	0.92	0.95	0.93	0.91	0.93	0.91	0.89	0.87		
光源形式 -	5	1.03	1.00	0.98	1.02	0.99	0.97	0.95	0.97	0.95	0.94	0.95	0.94	0.92	0.90		
器具光束 1,800 lm	7	1.05	1.03	1.02	1.04	1.02	1.01	0.99	1.00	0.99	0.97	0.98	0.97	0.96	0.93		
	10	1.07	1.06	1.04	1.05	1.04	1.03	1.02	1.02	1.01	1.01	1.00	1.00	0.99	0.96		


器具効率 Ft= 100%					
上方光束 Fu= 0%					
下方光束 Fd= 100%					
最大取付間隔					
A-A		1.28 H			
B-B		H			
保守率	良	0.79			
	中	0.75			
	否	0.67			
光度 (cd/1000 lm)					
	A-0	B-B	C-0	A'-0	C'-0
0	419				
10	414				
20	398				
30	363				
40	307				
50	236				
60	131				
70	22				
80	4				
90					
100					
110					
120					
130					
140					
150					
160					
170					
180					

単体照度分布(初期値)



単位: 水平距離(m)

配光曲線
(cd/1000 lm)



単位: 光度