

日立照明器具 照明特性																
名称: 直管形LED搭載器具	反射率	天井	80%			70%			50%			30%				
	壁	70%	50%	30%	70%	50%	30%	10%	50%	30%	10%	50%	30%	10%		
形式: WNME2101-J14AA	床	10%												0%		
	室指数	照明率 S/H=1.0														
<備考>		0.6	0.50	0.38	0.30	0.48	0.37	0.30	0.24	0.34	0.28	0.23	0.32	0.26	0.22	0.19
		0.8	0.58	0.47	0.39	0.56	0.45	0.38	0.32	0.42	0.36	0.31	0.39	0.34	0.29	0.26
姿図		1	0.64	0.53	0.45	0.61	0.51	0.44	0.38	0.48	0.41	0.36	0.44	0.39	0.34	0.30
		1.25	0.70	0.59	0.51	0.67	0.57	0.50	0.44	0.53	0.47	0.42	0.49	0.44	0.40	0.35
		1.5	0.74	0.64	0.57	0.71	0.62	0.55	0.50	0.58	0.52	0.47	0.54	0.49	0.45	0.40
		2	0.79	0.71	0.64	0.76	0.69	0.62	0.57	0.64	0.59	0.54	0.59	0.55	0.51	0.46
		2.5	0.83	0.75	0.69	0.79	0.73	0.67	0.62	0.68	0.63	0.59	0.63	0.59	0.56	0.50
		3	0.85	0.79	0.73	0.82	0.76	0.71	0.66	0.71	0.66	0.63	0.66	0.62	0.59	0.53
光源		4	0.88	0.83	0.78	0.85	0.80	0.76	0.72	0.75	0.71	0.68	0.70	0.67	0.64	0.57
品名	直管形LEDランプ	5	0.90	0.86	0.82	0.87	0.83	0.79	0.76	0.78	0.74	0.72	0.72	0.70	0.67	0.61
形式	LDK20SS-N/10/13NA	7	0.93	0.90	0.86	0.90	0.87	0.84	0.81	0.81	0.79	0.76	0.76	0.74	0.72	0.65
光束	1,300 lm	10	0.95	0.93	0.90	0.92	0.90	0.88	0.86	0.84	0.82	0.81	0.79	0.77	0.76	0.69
器具効率 Ft=	96.1%															
上方光束 Fu=	17.2%															
下方光束 Fd=	78.9%															
最大取付間隔																
A-A	1.38 H															
B-B	1.24 H															
保守率	良	0.86														
	中	0.81														
	否	0.72														
光度(cd/1000 lm)																
	A-0	B-B	C-0	A'-0	C'-0											
0	212	212	212													
10	211	208	209													
20	204	193	200													
30	193	173	184													
40	184	151	166													
50	168	117	145													
60	153	89	124													
70	137	51	103													
80	116	21	82													
90	99		65													
100	83		52													
110	67		40													
120	52		35													
130	47		22													
140	23		1													
150	1		1													
160	1		1													
170	1		1													
180																

