

日立照明器具 照明特性

名称: 直管形LED搭載器具	反射率	天井	80%			70%			50%			30%			0%					
		壁	70%	50%	30%	70%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0%				
		床	10%												0%					
形式: WNME4101-JM14AE2		室指数 照明率 S/H=1.0																		
<備考>		0.6	0.51	0.39	0.31	0.49	0.38	0.30	0.25	0.35	0.29	0.24	0.33	0.27	0.23	0.20				
		0.8	0.60	0.48	0.40	0.57	0.46	0.39	0.33	0.43	0.37	0.32	0.40	0.35	0.30	0.27				
姿図		1	0.65	0.54	0.46	0.63	0.52	0.45	0.39	0.49	0.42	0.37	0.45	0.40	0.35	0.31				
		1.25	0.71	0.60	0.53	0.68	0.58	0.51	0.45	0.54	0.48	0.43	0.51	0.45	0.41	0.36				
		1.5	0.75	0.65	0.58	0.72	0.63	0.56	0.51	0.59	0.53	0.48	0.55	0.50	0.46	0.41				
		2	0.81	0.72	0.65	0.77	0.70	0.64	0.58	0.65	0.60	0.55	0.61	0.56	0.52	0.47				
		2.5	0.84	0.77	0.70	0.81	0.74	0.68	0.63	0.69	0.64	0.60	0.64	0.60	0.57	0.51				
		3	0.86	0.80	0.74	0.83	0.77	0.72	0.67	0.72	0.68	0.64	0.67	0.64	0.60	0.54				
光源		4	0.90	0.84	0.79	0.86	0.81	0.77	0.73	0.76	0.72	0.69	0.71	0.68	0.65	0.59				
品名	直管形LEDランプ	5	0.92	0.87	0.83	0.89	0.84	0.81	0.77	0.79	0.76	0.73	0.74	0.71	0.69	0.62				
形式	LDK40SS-D/17/26NE	7	0.94	0.91	0.88	0.91	0.88	0.85	0.82	0.83	0.80	0.78	0.77	0.75	0.73	0.66				
光束	2,620 lm	10	0.97	0.94	0.92	0.94	0.91	0.89	0.87	0.86	0.84	0.82	0.80	0.79	0.77	0.70				
器具効率 Ft= 97.3%		単体照度分布(初期値)																		
上方光束 Fu= 17.1%																				
下方光束 Fd= 80.2%																				
最大取付間隔																				
A-A 1.38 H																				
B-B 1.24 H																				
保	良	0.88																		
守	中	0.86																		
率	否	0.81																		
光度(cd/1000 lm)																				
A-0	B-B	C-0	A'-0	C'-0																
0	220	220	220																	
10	218	216	217																	
20	214	202	208																	
30	202	182	191																	
40	189	150	170																	
50	175	119	149																	
60	155	86	128																	
70	133	49	102																	
80	115	21	82																	
90	95	2	64																	
100	77		49																	
110	64		39																	
120	52		37																	
130	43		25																	
140	30		5																	
150	5		2																	
160	2																			
170																				
180																				