

日立照明器具 照明特性

名称: 直管形LED搭載器具	反射率	天井	80%			70%			50%			30%			0%				
		壁	70%	50%	30%	70%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0%			
		床	10%												0%				
形式: WPME4121-JM14AE2		室指数 照明率 S/H=1.0																	
<備考>		0.6	0.50	0.39	0.31	0.48	0.37	0.30	0.25	0.35	0.29	0.24	0.33	0.27	0.23	0.20			
		0.8	0.59	0.47	0.39	0.57	0.46	0.38	0.33	0.43	0.36	0.32	0.40	0.35	0.30	0.27			
姿図		1	0.65	0.54	0.46	0.62	0.52	0.45	0.39	0.49	0.42	0.37	0.45	0.40	0.36	0.32			
		1.25	0.70	0.60	0.52	0.67	0.58	0.51	0.45	0.54	0.48	0.43	0.51	0.45	0.41	0.37			
		1.5	0.74	0.65	0.57	0.71	0.63	0.56	0.50	0.59	0.53	0.48	0.55	0.50	0.46	0.41			
		2	0.80	0.72	0.65	0.77	0.69	0.63	0.58	0.65	0.60	0.55	0.61	0.56	0.52	0.47			
		2.5	0.83	0.76	0.70	0.80	0.73	0.68	0.63	0.69	0.64	0.60	0.64	0.60	0.57	0.51			
		3	0.85	0.79	0.73	0.82	0.76	0.71	0.67	0.72	0.67	0.64	0.67	0.64	0.60	0.54			
光源		4	0.89	0.83	0.79	0.86	0.81	0.76	0.72	0.76	0.72	0.69	0.71	0.68	0.65	0.59			
品名	直管形LEDランプ	5	0.91	0.86	0.82	0.88	0.84	0.80	0.76	0.79	0.75	0.72	0.74	0.71	0.69	0.62			
形式	LDK40SS-D/15/23NE	7	0.93	0.90	0.87	0.90	0.87	0.84	0.82	0.82	0.80	0.77	0.77	0.75	0.73	0.67			
光束	2,330 lm	10	0.96	0.93	0.91	0.93	0.90	0.88	0.86	0.85	0.83	0.82	0.80	0.79	0.77	0.71			
器具効率 Ft= 95.9%		単体照度分布(初期値)																	
上方光束 Fu= 15.3%																			
下方光束 Fd= 80.5%																			
最大取付間隔																			
保守率	良	0.88																	
	中	0.86																	
	否	0.81																	
光度(cd/1000 lm)																			
	A-0	B-B	C-0	A'-0	C'-0														
0	223	223	223																
10	220	220	219																
20	215	207	211																
30	203	185	194																
40	188	155	171																
50	173	121	150																
60	155	87	126																
70	135	50	103																
80	113	21	82																
90	94		63																
100	76		48																
110	62		39																
120	49		29																
130	36		14																
140	18																		
150																			
160																			
170																			
180																			