




日立照明器具 照明特性

名称: 高天井用LEDランプ (アームタイプ)	反射率	天井	80%			70%				50%			30%			0%
		壁	70%	50%	30%	70%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0%
		床	10%													
形式: WSBME1601MNC	室指数	固有照明率 S/H=1.0														
<備考>	0.6	0.62	0.50	0.43	0.60	0.50	0.43	0.38	0.49	0.43	0.38	0.48	0.42	0.38	0.36	
	0.8	0.72	0.61	0.54	0.70	0.61	0.54	0.49	0.60	0.54	0.49	0.58	0.53	0.49	0.47	
姿図 	1	0.78	0.69	0.62	0.77	0.68	0.62	0.57	0.67	0.61	0.57	0.65	0.60	0.56	0.54	
	1.25	0.84	0.76	0.70	0.83	0.75	0.69	0.65	0.73	0.68	0.64	0.72	0.67	0.64	0.62	
	1.5	0.88	0.81	0.75	0.87	0.80	0.75	0.71	0.78	0.74	0.70	0.77	0.73	0.69	0.67	
	2	0.94	0.88	0.83	0.92	0.87	0.82	0.79	0.85	0.81	0.78	0.83	0.80	0.77	0.75	
	2.5	0.96	0.91	0.87	0.95	0.90	0.87	0.83	0.89	0.85	0.82	0.87	0.84	0.81	0.79	
	3	0.98	0.94	0.90	0.97	0.93	0.89	0.86	0.91	0.88	0.85	0.89	0.86	0.84	0.82	
	4	1.01	0.97	0.94	0.99	0.96	0.93	0.91	0.94	0.92	0.90	0.92	0.90	0.88	0.86	
光源形式 -	5	1.02	1.00	0.97	1.01	0.99	0.96	0.94	0.97	0.95	0.93	0.94	0.93	0.91	0.89	
器具光束 16,100 lm	7	1.05	1.03	1.01	1.03	1.02	1.00	0.98	0.99	0.98	0.97	0.97	0.96	0.95	0.92	
	10	1.06	1.05	1.04	1.05	1.04	1.03	1.02	1.02	1.01	1.00	1.00	0.99	0.98	0.95	
器具効率 Ft= 100%		単体照度分布(初期値) 														
上方光束 Fu= 0%																
下方光束 Fd= 100%																
最大取付間隔																
A-A 1.44 H																
B-B H																
保守率	良	0.81														
	中	0.79														
	否	0.75														
光度 (cd/1000 lm)		配光曲線 (cd/1000 lm) 														
	A-0	B-B	C-0	A'-0	C'-0											
0	371															
10	370															
20	373															
30	363															
40	318															
50	222															
60	126															
70	50															
80																
90																
100																
110																
120																
130																
140																
150																
160																
170																
180																