




日立照明器具 照明特性

形式: LDE1020S +LDA6D-G/40A		天井	80%			70%				50%			30%			0%
		壁	70%	50%	30%	70%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0%
		床	10%													
		室指数	照明率 S/H=1.0													
姿図 		0.6	0.51	0.44	0.39	0.50	0.43	0.39	0.36	0.43	0.39	0.36	0.42	0.38	0.35	0.34
		0.8	0.58	0.52	0.47	0.57	0.51	0.47	0.44	0.50	0.46	0.44	0.49	0.46	0.43	0.42
		1	0.62	0.57	0.52	0.62	0.56	0.52	0.49	0.55	0.52	0.49	0.54	0.51	0.49	0.47
		1.25	0.66	0.61	0.57	0.65	0.61	0.57	0.54	0.59	0.56	0.54	0.58	0.56	0.53	0.52
		1.5	0.69	0.64	0.61	0.68	0.64	0.61	0.58	0.63	0.60	0.58	0.62	0.59	0.57	0.56
		2	0.72	0.69	0.66	0.71	0.68	0.65	0.63	0.67	0.64	0.62	0.65	0.63	0.62	0.60
		2.5	0.74	0.71	0.68	0.73	0.70	0.68	0.66	0.69	0.67	0.65	0.68	0.66	0.64	0.63
		3	0.75	0.72	0.70	0.74	0.72	0.69	0.68	0.70	0.68	0.67	0.69	0.67	0.66	0.64
光源		4	0.76	0.74	0.72	0.75	0.74	0.72	0.70	0.72	0.71	0.69	0.71	0.69	0.68	0.67
品名	LED電球	5	0.77	0.76	0.74	0.77	0.75	0.74	0.72	0.73	0.72	0.71	0.72	0.71	0.70	0.68
形式	LDA6D-G/40A	7	0.79	0.78	0.77	0.78	0.77	0.76	0.75	0.75	0.75	0.74	0.74	0.73	0.73	0.71
光束	485 lm	10	0.80	0.79	0.79	0.79	0.78	0.78	0.77	0.77	0.76	0.76	0.75	0.75	0.75	0.73
器具効率 Ft= 74.6%			単体照度分布(初期) 													
上方光束 Fu= 0.0%																
下方光束 Fd= 74.6%																
配光分類																
BZ-																
最大取付間隔																
A-A 1.18 H																
B-B H																
保守率	良	0.63														
	中	0.60														
	否	0.53														
光度 (cd/1000 lm)																
	A-0	B-B	C-0	A'-0	C'-0	配光曲線 										
0	415															
10	407															
20	367															
30	328															
40	234															
50	135															
60	59															
70	9															
80																
90																
100																
110																
120																
130																
140																
150																
160																
170																
180																