


日立照明器具 照明特性

形式：LDE1020WB +LDA11D-G/100C		反射率	天井	80%			70%				50%			30%			0%
	壁		70%	50%	30%	70%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0%	
	床		10%														0%
	室指数		照明率 S/H=1.0														
姿図 	0.6	0.40	0.32	0.27	0.39	0.31	0.27	0.23	0.31	0.26	0.23	0.30	0.26	0.23	0.22		
	0.8	0.47	0.39	0.34	0.46	0.39	0.34	0.30	0.38	0.33	0.30	0.37	0.33	0.30	0.28		
	1	0.51	0.44	0.39	0.50	0.44	0.39	0.35	0.43	0.38	0.35	0.42	0.38	0.35	0.33		
	1.25	0.55	0.49	0.44	0.54	0.48	0.44	0.40	0.47	0.43	0.40	0.46	0.43	0.40	0.38		
	1.5	0.58	0.53	0.48	0.57	0.52	0.48	0.45	0.51	0.47	0.44	0.50	0.46	0.44	0.42		
	2	0.62	0.58	0.54	0.61	0.57	0.53	0.50	0.56	0.52	0.50	0.54	0.52	0.49	0.48		
	2.5	0.65	0.60	0.57	0.63	0.60	0.57	0.54	0.58	0.56	0.53	0.57	0.55	0.53	0.51		
	3	0.66	0.62	0.59	0.65	0.62	0.59	0.56	0.60	0.58	0.56	0.59	0.57	0.55	0.53		
	4	0.68	0.65	0.63	0.67	0.64	0.62	0.60	0.63	0.61	0.59	0.61	0.60	0.58	0.56		
品名	LED電球	5	0.69	0.67	0.65	0.68	0.66	0.64	0.62	0.65	0.63	0.62	0.63	0.62	0.61	0.59	
形式	LDA11D-G/100C	7	0.71	0.69	0.68	0.70	0.68	0.67	0.66	0.67	0.66	0.65	0.65	0.64	0.64	0.62	
光束	1,520 lm	10	0.72	0.71	0.70	0.71	0.70	0.69	0.68	0.69	0.68	0.67	0.67	0.67	0.66	0.64	

器具効率 Ft= 68.3%

上方光束 Fu= 0.0%

下方光束 Fd= 68.3%

配光分類

BZ-

最大取付間隔

A-A 1.34 H

B-B H

保守率	良	中	否
	0.63	0.60	0.53

光度 (cd/1000 lm)

	A-0	B-B	C-0	A'-0	C'-0
0	235				
10	230				
20	219				
30	210				
40	190				
50	153				
60	104				
70	54				
80	20				
90					
100					
110					
120					
130					
140					
150					
160					
170					
180					

単体照度分布(初期)

