


日立照明器具 照明特性

形式：LDE1020WB +LDA7D-G/60E		反射率	天井	80%			70%				50%			30%			0%	
			壁	70%	50%	30%	70%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0%	
			床	10%														0%
			室指数	照明率 S/H=1.0														
姿図 		0.6	0.41	0.34	0.29	0.40	0.33	0.29	0.26	0.33	0.28	0.26	0.32	0.28	0.25	0.24		
		0.8	0.47	0.41	0.36	0.46	0.40	0.36	0.33	0.39	0.35	0.32	0.38	0.35	0.32	0.31		
		1	0.51	0.45	0.41	0.50	0.45	0.41	0.37	0.44	0.40	0.37	0.43	0.40	0.37	0.36		
		1.25	0.55	0.50	0.46	0.54	0.49	0.45	0.42	0.48	0.45	0.42	0.47	0.44	0.42	0.40		
		1.5	0.58	0.53	0.49	0.57	0.52	0.49	0.46	0.51	0.48	0.46	0.50	0.47	0.45	0.44		
		2	0.61	0.57	0.54	0.60	0.57	0.54	0.51	0.55	0.53	0.51	0.54	0.52	0.50	0.49		
		2.5	0.63	0.60	0.57	0.62	0.59	0.56	0.54	0.58	0.55	0.53	0.56	0.55	0.53	0.51		
		3	0.64	0.61	0.59	0.63	0.61	0.58	0.56	0.59	0.57	0.55	0.58	0.56	0.55	0.53		
光 源		4	0.66	0.64	0.62	0.65	0.63	0.61	0.59	0.61	0.60	0.58	0.60	0.59	0.58	0.56		
品名	LED電球	5	0.67	0.65	0.63	0.66	0.64	0.63	0.61	0.63	0.62	0.60	0.62	0.61	0.59	0.58		
形式	LDA7D-G/60E	7	0.68	0.67	0.66	0.68	0.66	0.65	0.64	0.65	0.64	0.63	0.64	0.63	0.62	0.60		
光束	810 lm	10	0.69	0.69	0.68	0.69	0.68	0.67	0.66	0.66	0.66	0.65	0.65	0.65	0.64	0.62		

器具効率 $F_t = 65.4\%$

上方光束 $F_u = 0.0\%$

下方光束 $F_d = 65.4\%$

配光分類

BZ-

最大取付間隔

A-A 1.26 H

B-B H

保守率	良	中	否
	0.63	0.60	0.53

光度 (cd/1000 lm)

	A-0	B-B	C-0	A'-0	C'-0
0	274				
10	271				
20	255				
30	233				
40	192				
50	140				
60	80				
70	35				
80	9				
90					
100					
110					
120					
130					
140					
150					
160					
170					
180					

単体照度分布(初期)

