


日立照明器具 照明特性

形式：LDE1030S +LDA7D-G/D/60C		反 射 率	天井	80%			70%				50%			30%			0%
			壁	70%	50%	30%	70%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0%
			床	10%													0%
		室指数	照明率 S/H=1.0														
姿図 	0.6	0.52	0.45	0.40	0.51	0.44	0.40	0.37	0.44	0.39	0.36	0.43	0.39	0.36	0.35		
	0.8	0.59	0.53	0.48	0.58	0.52	0.48	0.45	0.51	0.48	0.45	0.51	0.47	0.44	0.43		
	1	0.64	0.58	0.54	0.63	0.57	0.53	0.50	0.56	0.53	0.50	0.55	0.52	0.50	0.48		
	1.25	0.68	0.62	0.59	0.67	0.62	0.58	0.55	0.61	0.58	0.55	0.60	0.57	0.55	0.53		
	1.5	0.70	0.66	0.62	0.69	0.65	0.62	0.59	0.64	0.61	0.59	0.63	0.60	0.58	0.57		
	2	0.74	0.70	0.67	0.73	0.69	0.67	0.64	0.68	0.66	0.64	0.67	0.65	0.63	0.62		
	2.5	0.76	0.72	0.70	0.75	0.72	0.69	0.67	0.70	0.68	0.66	0.69	0.67	0.66	0.64		
	3	0.77	0.74	0.72	0.76	0.73	0.71	0.69	0.72	0.70	0.68	0.70	0.69	0.67	0.66		
光 源		4	0.78	0.76	0.74	0.77	0.75	0.73	0.72	0.74	0.72	0.71	0.72	0.71	0.70	0.68	
品名	LED電球	5	0.79	0.77	0.76	0.78	0.77	0.75	0.74	0.75	0.74	0.73	0.74	0.73	0.72	0.70	
形式	LDA7D-G/D/60C	7	0.81	0.79	0.78	0.80	0.79	0.78	0.77	0.77	0.76	0.75	0.76	0.75	0.74	0.72	
光束	810 lm	10	0.82	0.81	0.80	0.81	0.80	0.80	0.79	0.79	0.78	0.78	0.77	0.77	0.76	0.74	

器具効率 Ft=	76.3%
上方光束 Fu=	0.0%
下方光束 Fd=	76.3%
配光分類	BZ-
最大取付間隔	
A-A	1.32 H
B-B	H
保守率	良 0.63 中 0.60 否 0.53

単体照度分布(初期)



光度 (cd/1000 lm)	A-0	B-B	C-0	A'-0	C'-0
0	381				
10	395				
20	385				
30	340				
40	266				
50	112				
60	55				
70	16				
80					
90					
100					
110					
120					
130					
140					
150					
160					
170					
180					

