


日立照明器具 照明特性

形式：LDE1030WB +LDA11D-G/100C		反射率	天井	80%			70%				50%			30%			0%
			壁	70%	50%	30%	70%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0%
			床	10%													0%
		室指数	照明率 S/H=1.0														
姿図 		0.6	0.43	0.33	0.27	0.42	0.33	0.27	0.23	0.32	0.27	0.23	0.31	0.27	0.23	0.22	
		0.8	0.50	0.41	0.35	0.49	0.41	0.35	0.31	0.40	0.35	0.31	0.39	0.34	0.31	0.29	
		1	0.55	0.47	0.41	0.54	0.46	0.41	0.37	0.45	0.40	0.36	0.44	0.40	0.36	0.34	
		1.25	0.60	0.52	0.47	0.58	0.52	0.46	0.42	0.50	0.46	0.42	0.49	0.45	0.42	0.40	
		1.5	0.63	0.57	0.51	0.62	0.56	0.51	0.47	0.54	0.50	0.47	0.53	0.49	0.46	0.44	
		2	0.67	0.62	0.58	0.66	0.61	0.57	0.54	0.60	0.56	0.53	0.58	0.55	0.52	0.51	
		2.5	0.70	0.65	0.61	0.69	0.65	0.61	0.58	0.63	0.60	0.57	0.61	0.59	0.56	0.54	
		3	0.72	0.68	0.64	0.71	0.67	0.64	0.61	0.65	0.62	0.60	0.64	0.61	0.59	0.57	
		4	0.74	0.71	0.68	0.73	0.70	0.67	0.65	0.68	0.66	0.64	0.67	0.65	0.63	0.61	
品名	LED電球	5	0.76	0.73	0.70	0.74	0.72	0.70	0.68	0.70	0.68	0.67	0.69	0.67	0.66	0.64	
形式	LDA11D-G/100C	7	0.77	0.75	0.74	0.76	0.75	0.73	0.71	0.73	0.72	0.70	0.71	0.70	0.69	0.67	
光束	1,520 lm	10	0.79	0.78	0.76	0.78	0.77	0.75	0.74	0.75	0.74	0.73	0.73	0.73	0.72	0.70	

器具効率 Ft= 74.9%

上方光束 Fu= 0.0%

下方光束 Fd= 74.9%

配光分類

BZ-

最大取付間隔

A-A 1.44 H

B-B H

保守率	良	中	否
	0.63	0.60	0.53

光度 (cd/1000 lm)

	A-0	B-B	C-0	A'-0	C'-0
0	222				
10	222				
20	219				
30	212				
40	200				
50	176				
60	124				
70	68				
80	26				
90					
100					
110					
120					
130					
140					
150					
160					
170					
180					

単体照度分布(初期)

