

日立照明器具 照明特性

名称: 高天井LED器具 MTE0903WN(A)	反射率	天井	80%			70%			50%			30%			0%	
		壁	70%	50%	30%	70%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0%
		床	10%												0%	
室指数 照明率 S/H=1.0																
<備考> 水銀ランプ250クラス (ビームの開き角:110°)	0.6	0.60	0.48	0.41	0.59	0.48	0.40	0.35	0.47	0.40	0.35	0.46	0.40	0.35	0.33	
	0.8	0.70	0.59	0.52	0.69	0.58	0.51	0.46	0.57	0.51	0.46	0.56	0.50	0.46	0.44	
姿図	1	0.77	0.67	0.60	0.75	0.66	0.59	0.54	0.64	0.58	0.54	0.63	0.58	0.53	0.51	
	1.25	0.83	0.74	0.67	0.81	0.73	0.67	0.62	0.71	0.66	0.61	0.70	0.65	0.61	0.59	
	1.5	0.87	0.79	0.73	0.86	0.78	0.73	0.68	0.77	0.72	0.67	0.75	0.71	0.67	0.65	
	2	0.93	0.86	0.81	0.91	0.85	0.80	0.76	0.83	0.79	0.76	0.82	0.78	0.75	0.73	
	2.5	0.96	0.90	0.86	0.94	0.89	0.85	0.81	0.87	0.84	0.81	0.85	0.82	0.80	0.77	
	3	0.98	0.93	0.89	0.96	0.92	0.88	0.85	0.90	0.87	0.84	0.88	0.85	0.83	0.80	
光源	4	1.01	0.97	0.94	0.99	0.96	0.93	0.90	0.94	0.91	0.89	0.92	0.89	0.87	0.85	
品名	LED	5	1.02	0.99	0.97	1.01	0.98	0.96	0.93	0.96	0.94	0.92	0.94	0.92	0.91	0.88
形式	-	7	1.05	1.02	1.00	1.03	1.01	1.00	0.98	0.99	0.98	0.96	0.97	0.96	0.95	0.92
光束	9,000 lm	10	1.06	1.05	1.04	1.05	1.04	1.02	1.01	1.02	1.00	1.00	0.99	0.99	0.98	0.95
器具効率 Ft=	100.0%															
上方光束 Fu=	0.0%															
下方光束 Fd=	100.0%															
最大取付間隔																
A-A	1.34	H														
B-B		H														
保守率	良	0.81														
	中	0.79														
	否	0.75														
光度(cd/1000 lm)																
	A-0	B-B	C-0	A'-0	C'-0											
0	359															
10	355															
20	343															
30	322															
40	287															
50	237															
60	160															
70	62															
80	5															
90																
100																
110																
120																
130																
140																
150																
160																
170																
180																

