



日立照明器具 照明特性

名称: 高天井LED器具		天井	80%			70%				50%			30%			0%		
			壁	70%	50%	30%	70%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0%	
形式: MTE2203NN(A) (W(S)MTE2203NN(A))		床	10%														0%	
			照明率 S/H=1.0															
<備考> メタルハライドランプ400クラス (ビームの開き角:60°)			0.6	0.80	0.73	0.68	0.79	0.73	0.68	0.65	0.72	0.68	0.65	0.71	0.68	0.65	0.64	
			0.8	0.87	0.81	0.77	0.86	0.81	0.77	0.74	0.80	0.76	0.74	0.79	0.76	0.73	0.72	
姿図 		1	0.92	0.86	0.82	0.91	0.86	0.82	0.79	0.85	0.81	0.79	0.84	0.81	0.78	0.77		
		1.25	0.95	0.90	0.87	0.94	0.90	0.86	0.84	0.89	0.86	0.83	0.87	0.85	0.83	0.81		
		1.5	0.98	0.94	0.90	0.97	0.93	0.90	0.87	0.91	0.89	0.87	0.90	0.88	0.86	0.84		
		2	1.01	0.97	0.95	1.00	0.97	0.94	0.92	0.95	0.93	0.91	0.94	0.92	0.90	0.88		
		2.5	1.02	0.99	0.97	1.01	0.98	0.96	0.94	0.97	0.95	0.93	0.95	0.94	0.92	0.90		
		3	1.03	1.01	0.98	1.02	1.00	0.98	0.96	0.98	0.96	0.95	0.96	0.95	0.94	0.92		
		4	1.04	1.02	1.01	1.03	1.01	1.00	0.98	1.00	0.98	0.97	0.98	0.97	0.96	0.93		
光源		5	1.05	1.04	1.02	1.04	1.03	1.01	1.00	1.01	1.00	0.99	0.99	0.98	0.97	0.95		
品名: LED		7	1.07	1.06	1.05	1.06	1.05	1.04	1.03	1.03	1.02	1.01	1.01	1.00	1.00	0.97		
形式: -		10	1.08	1.07	1.07	1.07	1.06	1.06	1.05	1.04	1.04	1.03	1.02	1.02	1.01	0.99		
光束: 21,900 lm																		

器具効率 Ft= 100.0%					
上方光束 Fu= 0.0%					
下方光束 Fd= 100.0%					
最大取付間隔					
A-A		0.96 H			
B-B		H			
保守率	良	0.81			
	中	0.79			
	否	0.75			
光度 (cd/1000 lm)					
	A-0	B-B	C-0	A'-0	C'-0
0	932				
10	896				
20	766				
30	512				
40	241				
50	66				
60	16				
70	5				
80					
90					
100					
110					
120					
130					
140					
150					
160					
170					
180					

単体照度分布 (初期値)



配光曲線
(cd/1000 lm)

