



日立照明器具 照明特性

名称: 高天井LED器具		天井	80%			70%				50%			30%			0%		
			壁	70%	50%	30%	70%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0%	
形式: MTE2803MN(A) (W(S)MTE2803MN(A))		床	10%															0%
			照明率 S/H=1.0															
<備考> 水銀ランプ700クラス (ビームの開き角:90°) 姿図 		室指数	0.6	0.66	0.56	0.50	0.65	0.56	0.50	0.45	0.55	0.49	0.45	0.54	0.49	0.45	0.43	
			0.8	0.76	0.67	0.61	0.75	0.66	0.60	0.56	0.65	0.60	0.56	0.64	0.59	0.56	0.54	
			1	0.82	0.74	0.68	0.81	0.73	0.68	0.64	0.72	0.67	0.63	0.71	0.66	0.63	0.61	
			1.25	0.88	0.80	0.75	0.86	0.80	0.74	0.70	0.78	0.74	0.70	0.77	0.73	0.69	0.68	
			1.5	0.91	0.85	0.80	0.90	0.84	0.80	0.76	0.83	0.79	0.75	0.81	0.78	0.75	0.73	
			2	0.96	0.91	0.87	0.95	0.90	0.86	0.83	0.88	0.85	0.82	0.87	0.84	0.81	0.79	
			2.5	0.98	0.94	0.90	0.97	0.93	0.90	0.87	0.91	0.88	0.86	0.90	0.87	0.85	0.83	
			3	1.00	0.96	0.93	0.99	0.95	0.92	0.90	0.93	0.91	0.88	0.91	0.89	0.87	0.85	
			4	1.02	0.99	0.96	1.01	0.98	0.96	0.93	0.96	0.94	0.92	0.94	0.92	0.91	0.88	
			5	1.04	1.01	0.99	1.02	1.00	0.98	0.96	0.98	0.96	0.95	0.96	0.95	0.93	0.91	
品名: LED			7	1.05	1.04	1.02	1.04	1.03	1.01	1.00	1.01	0.99	0.98	0.99	0.98	0.97	0.94	
			10	1.07	1.06	1.05	1.06	1.05	1.04	1.03	1.03	1.02	1.01	1.01	1.00	0.99	0.97	
光束: 25,500 lm																		


器具効率 Ft= 100.0%					
上方光束 Fu= 0.0%					
下方光束 Fd= 100.0%					
最大取付間隔					
A-A		1.40 H			
B-B		H			
保守率	良	0.81			
	中	0.79			
	否	0.75			
光度 (cd/1000 lm)					
	A-0	B-B	C-0	A'-0	C'-0
0	398				
10	438				
20	514				
30	400				
40	306				
50	205				
60	97				
70	17				
80	1				
90					
100					
110					
120					
130					
140					
150					
160					
170					
180					

単体照度分布 (初期値)




0-200
200-400
400-600
600-800
800-1000

配光曲線
(cd/1000 lm)



A
B
C-C'

単体照度分布 (初期値)



配光曲線 (cd/1000 lm)

