

日立照明器具 照明特性

名称: 交換形LED逆富士 形 CP付		天井	80%			70%				50%			30%			0%																
			壁	70%	50%	30%	70%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0%															
形式: NC4A1CP		床	10%															0%														
			固有照明率 S/H=1.0																													
<備考>		0.6	0.57	0.45	0.37	0.55	0.44	0.36	0.31	0.42	0.36	0.31	0.41	0.35	0.31	0.28																
		0.8	0.66	0.54	0.46	0.64	0.53	0.46	0.40	0.52	0.45	0.40	0.50	0.44	0.39	0.37																
姿図 		1	0.72	0.61	0.53	0.70	0.60	0.53	0.47	0.58	0.52	0.47	0.56	0.51	0.46	0.43																
		1.25	0.78	0.68	0.61	0.76	0.67	0.60	0.54	0.65	0.58	0.53	0.63	0.57	0.53	0.50																
		1.5	0.82	0.73	0.66	0.81	0.72	0.65	0.60	0.70	0.64	0.59	0.67	0.62	0.58	0.55																
		2	0.88	0.80	0.74	0.86	0.79	0.73	0.68	0.76	0.71	0.67	0.74	0.70	0.66	0.63																
		2.5	0.92	0.85	0.79	0.90	0.83	0.78	0.74	0.81	0.76	0.72	0.78	0.74	0.71	0.68																
		3	0.94	0.88	0.83	0.92	0.86	0.82	0.78	0.84	0.80	0.76	0.81	0.77	0.74	0.71																
光源形式		4	0.97	0.92	0.88	0.95	0.91	0.87	0.83	0.88	0.84	0.81	0.85	0.82	0.80	0.76																
CE404NE-C14A		5	0.99	0.95	0.91	0.97	0.94	0.90	0.87	0.91	0.88	0.85	0.88	0.85	0.83	0.80																
器具光束		7	1.02	0.99	0.96	1.00	0.97	0.95	0.92	0.94	0.92	0.90	0.91	0.90	0.88	0.84																
4,400 lm		10	1.04	1.02	1.00	1.02	1.00	0.98	0.96	0.97	0.95	0.94	0.94	0.93	0.92	0.88																
器具効率 Ft= 100%			単体照度分布 (初期値) 																													
上方光束 Fu= 3.5%																																
下方光束 Fd= 96.5%																																
最大取付間隔																																
A-A 1.28 H																																
B-B 1.26 H																																
保守率	良	0.88																														
	中	0.86																														
	否	0.81																														
光度 (cd/1000 lm)																																
	A-0	B-B	C-0	A'-0	C'-0																											
0	318	318	318																													
10	312	313	313																													
20	296	295	296																													
30	271	268	268																													
40	239	232	235																													
50	197	189	191																													
60	154	136	148																													
70	110	89	102																													
80	69	35	54																													
90	41	5	25																													
100	21	5	12																													
110	13	3	6																													
120	5	2	1																													
130																																
140																																
150																																
160																																
170																																
180																																
			配光曲線 (cd/1000 lm) 																													