

日立照明器具 照明特性

名称: 交換形LED逆富士形 CP付	反射率	天井	80%			70%				50%			30%			0%	
		壁	70%	50%	30%	70%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0%	
		床	10%														0%
形式: NC4A1CP	室指数	固有照明率 S/H=1.0															
<div><備考></div> <div>姿図</div>	0.6	0.57	0.45	0.37	0.55	0.44	0.36	0.31	0.42	0.36	0.31	0.41	0.35	0.31	0.28		
	0.8	0.66	0.54	0.46	0.64	0.53	0.46	0.40	0.52	0.45	0.40	0.50	0.44	0.39	0.37		
	1	0.72	0.61	0.53	0.70	0.60	0.53	0.47	0.58	0.52	0.47	0.56	0.51	0.46	0.43		
	1.25	0.78	0.68	0.61	0.76	0.67	0.60	0.54	0.65	0.58	0.53	0.63	0.57	0.53	0.50		
	1.5	0.82	0.73	0.66	0.81	0.72	0.65	0.60	0.70	0.64	0.59	0.67	0.62	0.58	0.55		
	2	0.88	0.80	0.74	0.86	0.79	0.73	0.68	0.76	0.71	0.67	0.74	0.70	0.66	0.63		
	2.5	0.92	0.85	0.79	0.90	0.83	0.78	0.74	0.81	0.76	0.72	0.78	0.74	0.71	0.68		
	3	0.94	0.88	0.83	0.92	0.86	0.82	0.78	0.84	0.80	0.76	0.81	0.77	0.74	0.71		
光源形式	4	0.97	0.92	0.88	0.95	0.91	0.87	0.83	0.88	0.84	0.81	0.85	0.82	0.80	0.76		
CE405DG-X14A	5	0.99	0.95	0.91	0.97	0.94	0.90	0.87	0.91	0.88	0.85	0.88	0.85	0.83	0.80		
器具光束	7	1.02	0.99	0.96	1.00	0.97	0.95	0.92	0.94	0.92	0.90	0.91	0.90	0.88	0.84		
4,950 lm	10	1.04	1.02	1.00	1.02	1.00	0.98	0.96	0.97	0.95	0.94	0.94	0.93	0.92	0.88		

器具効率 Ft= 100%			<div>単体照度分布 (初期値)</div> <div>0-200</div> <div>200-400</div> <div>400-600</div> <div>600-800</div> <div>800-1000</div>																											
上方光束 Fu= 3.5%																														
下方光束 Fd= 96.5%																														
最大取付間隔			<div>配光曲線</div> <div>(cd/1000 lm)</div> <div>A</div> <div>B</div> <div>C-C'</div>																											
A-A 1.28 H																														
B-B 1.26 H																														
保守率	良	0.88																												
	中	0.86																												
	否	0.81																												
光度 (cd/1000 lm)																														
	A-0	B-B																												
0	318	318															318													
10	312	313															313													
20	296	295	296																											
30	271	268	268																											
40	239	232	235																											
50	197	189	191																											
60	154	136	148																											
70	110	89	102																											
80	69	35	54																											
90	41	5	25																											
100	21	5	12																											
110	13	3	6																											
120	5	2	1																											
130																														
140																														
150																														
160																														
170																														
180																														