




日立照明器具 照明特性

| | | | | | | | | | | | | | | | | | |
|---|---|--|---------------|------|------|------|------|------|------|------|------|------|------|------|------|------|----|
| 名称: 人感センサー付 交換形ベース器具 (逆富士形) | | 天井 反射率 | 80% | | | 70% | | | | 50% | | | 30% | | | 0% | |
| | | | 壁 | 70% | 50% | 30% | 70% | 50% | 30% | 10% | 50% | 30% | 10% | 50% | 30% | 10% | 0% |
| 形式: NC4B1SL | | 床 | 10% | | | | | | | | | | | | | | 0% |
| | | 室指数 | 固有照明率 S/H=1.0 | | | | | | | | | | | | | | |
| 〈備考〉 | | 0.6 | 0.57 | 0.45 | 0.37 | 0.55 | 0.44 | 0.36 | 0.31 | 0.42 | 0.36 | 0.31 | 0.41 | 0.35 | 0.31 | 0.28 | |
| | | 0.8 | 0.66 | 0.54 | 0.46 | 0.64 | 0.53 | 0.46 | 0.40 | 0.52 | 0.45 | 0.40 | 0.50 | 0.44 | 0.39 | 0.37 | |
| 姿図 | | 1 | 0.72 | 0.61 | 0.53 | 0.70 | 0.60 | 0.53 | 0.47 | 0.58 | 0.52 | 0.47 | 0.56 | 0.51 | 0.46 | 0.43 | |
|  | | 1.25 | 0.78 | 0.68 | 0.61 | 0.76 | 0.67 | 0.60 | 0.54 | 0.65 | 0.58 | 0.53 | 0.63 | 0.57 | 0.53 | 0.50 | |
| | | 1.5 | 0.82 | 0.73 | 0.66 | 0.81 | 0.72 | 0.65 | 0.60 | 0.70 | 0.64 | 0.59 | 0.67 | 0.62 | 0.58 | 0.55 | |
| | | 2 | 0.88 | 0.80 | 0.74 | 0.86 | 0.79 | 0.73 | 0.68 | 0.76 | 0.71 | 0.67 | 0.74 | 0.70 | 0.66 | 0.63 | |
| | | 2.5 | 0.92 | 0.85 | 0.79 | 0.90 | 0.83 | 0.78 | 0.74 | 0.81 | 0.76 | 0.72 | 0.78 | 0.74 | 0.71 | 0.68 | |
| | | 3 | 0.94 | 0.88 | 0.83 | 0.92 | 0.86 | 0.82 | 0.78 | 0.84 | 0.80 | 0.76 | 0.81 | 0.77 | 0.74 | 0.71 | |
| 光源形式 | | 4 | 0.97 | 0.92 | 0.88 | 0.95 | 0.91 | 0.87 | 0.83 | 0.88 | 0.84 | 0.81 | 0.85 | 0.82 | 0.80 | 0.76 | |
| CE402DE-X14A | | 5 | 0.99 | 0.95 | 0.91 | 0.97 | 0.94 | 0.90 | 0.87 | 0.91 | 0.88 | 0.85 | 0.88 | 0.85 | 0.83 | 0.80 | |
| 器具光束 | | 7 | 1.02 | 0.99 | 0.96 | 1.00 | 0.97 | 0.95 | 0.92 | 0.94 | 0.92 | 0.90 | 0.91 | 0.90 | 0.88 | 0.84 | |
| 2,090 lm | | 10 | 1.04 | 1.02 | 1.00 | 1.02 | 1.00 | 0.98 | 0.96 | 0.97 | 0.95 | 0.94 | 0.94 | 0.93 | 0.92 | 0.88 | |
| 器具効率 Ft= 100% | | 単位照度分布 (初期値) | | | | | | | | | | | | | | | |
| 上方光束 Fu= 3.5% | |  | | | | | | | | | | | | | | | |
| 下方光束 Fd= 96.5% | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | |
| 最大取付間隔 | | A-A 1.28 H B-B 1.26 H | | | | | | | | | | | | | | | |
| 保守率 | 良 | 0.88 | | | | | | | | | | | | | | | |
| | 中 | 0.86 | | | | | | | | | | | | | | | |
| | 否 | 0.81 | | | | | | | | | | | | | | | |
| 光度 (cd/1000 lm) | | A-0 B-B C-0 A'-0 C'-0 | | | | | | | | | | | | | | | |
| 0 | | 318 318 318 | | | | | | | | | | | | | | | |
| 10 | | 312 313 313 | | | | | | | | | | | | | | | |
| 20 | | 296 295 296 | | | | | | | | | | | | | | | |
| 30 | | 271 268 268 | | | | | | | | | | | | | | | |
| 40 | | 239 232 235 | | | | | | | | | | | | | | | |
| 50 | | 197 189 191 | | | | | | | | | | | | | | | |
| 60 | | 154 136 148 | | | | | | | | | | | | | | | |
| 70 | | 110 89 102 | | | | | | | | | | | | | | | |
| 80 | | 69 35 54 | | | | | | | | | | | | | | | |
| 90 | | 41 5 25 | | | | | | | | | | | | | | | |
| 100 | | 21 5 12 | | | | | | | | | | | | | | | |
| 110 | | 13 3 6 | | | | | | | | | | | | | | | |
| 120 | | 5 2 1 | | | | | | | | | | | | | | | |
| 130 | | | | | | | | | | | | | | | | | |
| 140 | | | | | | | | | | | | | | | | | |
| 150 | | | | | | | | | | | | | | | | | |
| 160 | | | | | | | | | | | | | | | | | |
| 170 | | | | | | | | | | | | | | | | | |
| 180 | | | | | | | | | | | | | | | | | |
| 配光曲線 (cd/1000 lm) | |  | | | | | | | | | | | | | | | |