




# 日立照明器具 照明特性

|   |      |   |      |      |      |      |      |      |      |      |      |      |      |      |      |    |
|---|------|---|------|------|------|------|------|------|------|------|------|------|------|------|------|----|
| 名称: 交換形LED下面開放形   | 反射率  | 天井  | 80%  |      |      | 70%  |      |      |      | 50%  |      |      | 30%  |      |      | 0% |
|   |      | 壁   | 70%  | 50%  | 30%  | 70%  | 50%  | 30%  | 10%  | 50%  | 30%  | 10%  | 50%  | 30%  | 10%  | 0% |
|   |      | 床   | 10%  |      |      |      |      |      |      |      |      |      |      |      |      |    |
| 形式: NC4C1   | 室指数  | 固有照明率 S/H=1.0   |      |      |      |      |      |      |      |      |      |      |      |      |      |    |
| <備考>  | 0.6  | 0.57  | 0.45 | 0.37 | 0.56 | 0.45 | 0.37 | 0.32 | 0.43 | 0.37 | 0.32 | 0.42 | 0.36 | 0.32 | 0.30 |    |
|   | 0.8  | 0.67  | 0.55 | 0.47 | 0.65 | 0.54 | 0.47 | 0.41 | 0.53 | 0.46 | 0.41 | 0.52 | 0.46 | 0.41 | 0.39 |    |
| 姿図<br> | 1    | 0.73  | 0.62 | 0.54 | 0.71 | 0.61 | 0.54 | 0.48 | 0.60 | 0.53 | 0.48 | 0.58 | 0.52 | 0.48 | 0.45 |    |
|   | 1.25 | 0.79  | 0.69 | 0.62 | 0.77 | 0.68 | 0.61 | 0.56 | 0.66 | 0.60 | 0.55 | 0.65 | 0.59 | 0.55 | 0.52 |    |
|   | 1.5  | 0.83  | 0.74 | 0.67 | 0.82 | 0.73 | 0.67 | 0.62 | 0.71 | 0.66 | 0.61 | 0.70 | 0.65 | 0.60 | 0.58 |    |
|   | 2    | 0.89  | 0.82 | 0.75 | 0.87 | 0.80 | 0.75 | 0.70 | 0.78 | 0.73 | 0.69 | 0.76 | 0.72 | 0.68 | 0.66 |    |
|   | 2.5  | 0.92  | 0.86 | 0.81 | 0.91 | 0.85 | 0.80 | 0.75 | 0.83 | 0.78 | 0.74 | 0.81 | 0.77 | 0.74 | 0.71 |    |
|   | 3    | 0.95  | 0.89 | 0.84 | 0.93 | 0.88 | 0.83 | 0.79 | 0.86 | 0.82 | 0.78 | 0.84 | 0.80 | 0.77 | 0.75 |    |
| 光源形式  | 4    | 0.98  | 0.93 | 0.89 | 0.96 | 0.92 | 0.88 | 0.85 | 0.90 | 0.87 | 0.84 | 0.88 | 0.85 | 0.83 | 0.80 |    |
| CE407NG-C14A  | 5    | 1.00  | 0.96 | 0.93 | 0.98 | 0.95 | 0.92 | 0.89 | 0.93 | 0.90 | 0.88 | 0.91 | 0.88 | 0.86 | 0.83 |    |
| 器具光束  | 7    | 1.02  | 1.00 | 0.97 | 1.01 | 0.99 | 0.96 | 0.94 | 0.96 | 0.94 | 0.92 | 0.94 | 0.92 | 0.91 | 0.88 |    |
| 6,820 lm  | 10   | 1.04  | 1.02 | 1.01 | 1.03 | 1.01 | 1.00 | 0.98 | 0.99 | 0.98 | 0.96 | 0.97 | 0.96 | 0.95 | 0.92 |    |
| 器具効率 Ft= 100%   |      | <div>単体照度分布(初期値)</div>             |      |      |      |      |      |      |      |      |      |      |      |      |      |    |
| 上方光束 Fu= 0%   |      |   |      |      |      |      |      |      |      |      |      |      |      |      |      |    |
| 下方光束 Fd= 100%   |      |   |      |      |      |      |      |      |      |      |      |      |      |      |      |    |
|   |      |   |      |      |      |      |      |      |      |      |      |      |      |      |      |    |
| 最大取付間隔  |      | <div>配光曲線<br/>(cd/1000 lm)</div>  |      |      |      |      |      |      |      |      |      |      |      |      |      |    |
| A-A 1.28 H  |      |   |      |      |      |      |      |      |      |      |      |      |      |      |      |    |
| B-B 1.26 H  |      |   |      |      |      |      |      |      |      |      |      |      |      |      |      |    |
| 保守率   |      |   |      |      |      |      |      |      |      |      |      |      |      |      |      |    |
| 良   | 0.86 |   |      |      |      |      |      |      |      |      |      |      |      |      |      |    |
| 中   | 0.81 |   |      |      |      |      |      |      |      |      |      |      |      |      |      |    |
| 否   | 0.72 |   |      |      |      |      |      |      |      |      |      |      |      |      |      |    |
| 光度 (cd/1000 lm)   |      |   |      |      |      |      |      |      |      |      |      |      |      |      |      |    |
|   | A-0  | B-B   | C-0  | A'-0 | C'-0 |      |      |      |      |      |      |      |      |      |      |    |
| 0   | 333  | 333   | 333  |      |      |      |      |      |      |      |      |      |      |      |      |    |
| 10  | 326  | 329   | 327  |      |      |      |      |      |      |      |      |      |      |      |      |    |
| 20  | 311  | 309   | 309  |      |      |      |      |      |      |      |      |      |      |      |      |    |
| 30  | 284  | 283   | 283  |      |      |      |      |      |      |      |      |      |      |      |      |    |
| 40  | 250  | 243   | 246  |      |      |      |      |      |      |      |      |      |      |      |      |    |
| 50  | 207  | 197   | 201  |      |      |      |      |      |      |      |      |      |      |      |      |    |
| 60  | 167  | 145   | 155  |      |      |      |      |      |      |      |      |      |      |      |      |    |
| 70  | 118  | 90  | 110  |      |      |      |      |      |      |      |      |      |      |      |      |    |
| 80  | 63   | 32  | 54   |      |      |      |      |      |      |      |      |      |      |      |      |    |
| 90  |      |   |      |      |      |      |      |      |      |      |      |      |      |      |      |    |
| 100   |      |   |      |      |      |      |      |      |      |      |      |      |      |      |      |    |
| 110   |      |   |      |      |      |      |      |      |      |      |      |      |      |      |      |    |
| 120   |      |   |      |      |      |      |      |      |      |      |      |      |      |      |      |    |
| 130   |      |   |      |      |      |      |      |      |      |      |      |      |      |      |      |    |
| 140   |      |   |      |      |      |      |      |      |      |      |      |      |      |      |      |    |
| 150   |      |   |      |      |      |      |      |      |      |      |      |      |      |      |      |    |
| 160   |      |   |      |      |      |      |      |      |      |      |      |      |      |      |      |    |
| 170   |      |   |      |      |      |      |      |      |      |      |      |      |      |      |      |    |
| 180   |      |   |      |      |      |      |      |      |      |      |      |      |      |      |      |    |