







日立照明器具 照明特性

名称:交換形LED ウォールウォッシュ形		天井	80%			70%				50%			30%			0%					
			壁	70%	50%	30%	70%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0%				
形式:NC4D		床	10%															0%			
			固有照明率 S/H=1.0																		
＜備考＞		0.6	0.53	0.41	0.33	0.51	0.40	0.32	0.27	0.37	0.31	0.26	0.35	0.29	0.25	0.22					
		0.8	0.62	0.50	0.42	0.60	0.48	0.41	0.35	0.46	0.39	0.34	0.43	0.37	0.33	0.29					
姿図 		1	0.68	0.56	0.48	0.65	0.55	0.47	0.41	0.52	0.45	0.40	0.49	0.43	0.38	0.34					
		1.25	0.74	0.63	0.55	0.71	0.61	0.53	0.48	0.57	0.51	0.46	0.54	0.49	0.44	0.40					
		1.5	0.78	0.68	0.60	0.75	0.66	0.59	0.53	0.62	0.56	0.51	0.59	0.53	0.49	0.44					
		2	0.84	0.75	0.68	0.81	0.73	0.66	0.61	0.69	0.63	0.58	0.65	0.60	0.56	0.51					
		2.5	0.87	0.79	0.73	0.84	0.77	0.71	0.66	0.73	0.68	0.63	0.69	0.64	0.61	0.55					
		3	0.89	0.83	0.77	0.87	0.80	0.75	0.70	0.76	0.71	0.67	0.71	0.68	0.64	0.59					
光源形式 CET405NE-C14A		4	0.93	0.87	0.82	0.90	0.85	0.80	0.76	0.80	0.76	0.73	0.76	0.72	0.69	0.64					
		5	0.95	0.90	0.86	0.92	0.88	0.84	0.80	0.83	0.80	0.77	0.78	0.76	0.73	0.67					
器具光束 5,060 lm		7	0.98	0.94	0.91	0.95	0.92	0.89	0.86	0.87	0.84	0.82	0.82	0.80	0.78	0.72					
		10	1.00	0.97	0.95	0.97	0.95	0.93	0.90	0.90	0.88	0.86	0.85	0.84	0.82	0.76					
器具効率 Ft= 100%		単位照度分布 (初期値)																			
上方光束 Fu= 13.2%																					
下方光束 Fd= 86.8%																					
最大取付間隔																					
A-A 1.30 H																					
B-B 1.26 H																					
保守率	良	0.86																			
	中	0.81																			
	否	0.72																			
光度 (cd/1000 lm)																					
	A-0																	B-B	C-0	A'-0	C'-0
0	248																	248	248	248	248
10	279																	246	267	207	216
20	308																	231	281	160	179
30	322																	209	286	107	135
40	327																	179	278	66	91
50	322																	144	263	25	49
60	308																	107	238		14
70	281																	67	210		
80	243																	26	173		
90	207																	3	134		
100	157																	3	89		
110	107																	2	55		
120	69																	1	26		
130	35																	1	13		
140	17																	1	7		
150	7																	1	4		
160	4																	1	2		
170	4	2	2																		
180																					

単体照度分布(初期値)



配光曲線
(cd/1000 lm)

