







日立照明器具 照明特性

名称: 交換形LED ウォールウォッシュ形		天井	80%			70%				50%			30%			0%				
			壁	70%	50%	30%	70%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0%			
形式: NC4D		床	10%															0%		
			固有照明率 S/H=1.0																	
＜備考＞		室指数	0.6	0.53	0.41	0.33	0.51	0.40	0.32	0.27	0.37	0.31	0.26	0.35	0.29	0.25	0.22			
		0.8	0.62	0.50	0.42	0.60	0.48	0.41	0.35	0.46	0.39	0.34	0.43	0.37	0.33	0.29				
姿図 		1	0.68	0.56	0.48	0.65	0.55	0.47	0.41	0.52	0.45	0.40	0.49	0.43	0.38	0.34				
		1.25	0.74	0.63	0.55	0.71	0.61	0.53	0.48	0.57	0.51	0.46	0.54	0.49	0.44	0.40				
		1.5	0.78	0.68	0.60	0.75	0.66	0.59	0.53	0.62	0.56	0.51	0.59	0.53	0.49	0.44				
		2	0.84	0.75	0.68	0.81	0.73	0.66	0.61	0.69	0.63	0.58	0.65	0.60	0.56	0.51				
		2.5	0.87	0.79	0.73	0.84	0.77	0.71	0.66	0.73	0.68	0.63	0.69	0.64	0.61	0.55				
		3	0.89	0.83	0.77	0.87	0.80	0.75	0.70	0.76	0.71	0.67	0.71	0.68	0.64	0.59				
光源形式 CET406NE-N14A		4	0.93	0.87	0.82	0.90	0.85	0.80	0.76	0.80	0.76	0.73	0.76	0.72	0.69	0.64				
		5	0.95	0.90	0.86	0.92	0.88	0.84	0.80	0.83	0.80	0.77	0.78	0.76	0.73	0.67				
器具光束 5,840 lm		7	0.98	0.94	0.91	0.95	0.92	0.89	0.86	0.87	0.84	0.82	0.82	0.80	0.78	0.72				
		10	1.00	0.97	0.95	0.97	0.95	0.93	0.90	0.90	0.88	0.86	0.85	0.84	0.82	0.76				
器具効率 Ft= 100%			単位照度分布 (初期値)																	
上方光束 Fu= 13.2%																				
下方光束 Fd= 86.8%																				
最大取付間隔																				
A-A		1.30																H		
B-B		1.26																H		
保守率	良	0.86																		
	中	0.81																		
	否	0.72																		
光度 (cd/1000 lm)																				
	A-0	B-B																C-0	A'-0	C'-0
0	248	248																248	248	248
10	279	246																267	207	216
20	308	231																281	160	179
30	322	209																286	107	135
40	327	179																278	66	91
50	322	144																263	25	49
60	308	107																238		14
70	281	67																210		
80	243	26																173		
90	207	3																134		
100	157	3																89		
110	107	2																55		
120	69	1																26		
130	35	1																13		
140	17	1																7		
150	7	1																4		
160	4	1	2																	
170	4	2	2																	
180																				

単体照度分布(初期値)



配光曲線
(cd/1000 lm)

