





日立照明器具 照明特性

名称: 交換形LED逆富士形	天井	80%			70%				50%			30%			0%														
		壁	70%	50%	30%	70%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0%													
			床	10%													0%												
形式: NC8A	室指数	固有照明率 S/H=1.0																											
<備考>	0.6	0.57	0.45	0.37	0.55	0.44	0.36	0.31	0.42	0.36	0.31	0.41	0.35	0.31	0.28														
	0.8	0.66	0.54	0.46	0.64	0.53	0.46	0.40	0.52	0.45	0.40	0.50	0.44	0.39	0.37														
姿図 	1	0.72	0.61	0.53	0.70	0.60	0.53	0.47	0.58	0.52	0.47	0.56	0.51	0.46	0.43														
	1.25	0.78	0.68	0.61	0.76	0.67	0.60	0.54	0.65	0.58	0.53	0.63	0.57	0.53	0.50														
	1.5	0.82	0.73	0.66	0.81	0.72	0.65	0.60	0.70	0.64	0.59	0.67	0.62	0.58	0.55														
	2	0.88	0.80	0.74	0.86	0.79	0.73	0.68	0.76	0.71	0.67	0.74	0.70	0.66	0.63														
	2.5	0.92	0.85	0.79	0.90	0.83	0.78	0.74	0.81	0.76	0.72	0.78	0.74	0.71	0.68														
	3	0.94	0.88	0.83	0.92	0.86	0.82	0.78	0.84	0.80	0.76	0.81	0.77	0.74	0.71														
	4	0.97	0.92	0.88	0.95	0.91	0.87	0.83	0.88	0.84	0.81	0.85	0.82	0.80	0.76														
光源形式	5	0.99	0.95	0.91	0.97	0.94	0.90	0.87	0.91	0.88	0.85	0.88	0.85	0.83	0.80														
器具光束	7	1.02	0.99	0.96	1.00	0.97	0.95	0.92	0.94	0.92	0.90	0.91	0.90	0.88	0.84														
11,250 lm	10	1.04	1.02	1.00	1.02	1.00	0.98	0.96	0.97	0.95	0.94	0.94	0.93	0.92	0.88														
器具効率 Ft= 100%		<div>単体照度分布 (初期値)</div> 																											
上方光束 Fu= 3.5%																													
下方光束 Fd= 96.5%																													
最大取付間隔		<div>配光曲線 (cd/1000 lm)</div> 																											
A-A 1.28 H																													
B-B 1.26 H																													
保守率	良	0.88	<div>器具光束</div> 																										
	中	0.86																											
	否	0.81																											
光度 (cd/1000 lm)																													
	A-0	B-B															C-0	A'-0	C'-0										
0	318	318	318																										
10	312	313	313																										
20	296	295	296																										
30	271	268	268																										
40	239	232	235																										
50	197	189	191																										
60	154	136	148																										
70	110	89	102																										
80	69	35	54																										
90	41	5	25																										
100	21	5	12																										
110	13	3	6																										
120	5	2	1																										
130																													
140																													
150																													
160																													
170																													
180																													