






日立照明器具 照明特性

名称: 交換形LED ウォールウォッシュ形	天井	80%			70%				50%			30%			0%	
		壁	70%	50%	30%	70%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0%
			床	10%												
形式: NC8D	室指数	固有照明率 S/H=1.0														
＜備考＞	0.6	0.53	0.41	0.33	0.51	0.40	0.32	0.27	0.37	0.31	0.26	0.35	0.29	0.25	0.22	
	0.8	0.62	0.50	0.42	0.60	0.48	0.41	0.35	0.46	0.39	0.34	0.43	0.37	0.33	0.29	
姿図 	1	0.68	0.56	0.48	0.65	0.55	0.47	0.41	0.52	0.45	0.40	0.49	0.43	0.38	0.34	
	1.25	0.74	0.63	0.55	0.71	0.61	0.53	0.48	0.57	0.51	0.46	0.54	0.49	0.44	0.40	
	1.5	0.78	0.68	0.60	0.75	0.66	0.59	0.53	0.62	0.56	0.51	0.59	0.53	0.49	0.44	
	2	0.84	0.75	0.68	0.81	0.73	0.66	0.61	0.69	0.63	0.58	0.65	0.60	0.56	0.51	
	2.5	0.87	0.79	0.73	0.84	0.77	0.71	0.66	0.73	0.68	0.63	0.69	0.64	0.61	0.55	
	3	0.89	0.83	0.77	0.87	0.80	0.75	0.70	0.76	0.71	0.67	0.71	0.68	0.64	0.59	
光源形式	4	0.93	0.87	0.82	0.90	0.85	0.80	0.76	0.80	0.76	0.73	0.76	0.72	0.69	0.64	
CE808NE-N14A	5	0.95	0.90	0.86	0.92	0.88	0.84	0.80	0.83	0.80	0.77	0.78	0.76	0.73	0.67	
器具光束	7	0.98	0.94	0.91	0.95	0.92	0.89	0.86	0.87	0.84	0.82	0.82	0.80	0.78	0.72	
8,560 lm	10	1.00	0.97	0.95	0.97	0.95	0.93	0.90	0.90	0.88	0.86	0.85	0.84	0.82	0.76	
器具効率 Ft= 100%		単体照度分布 (初期値) 														
上方光束 Fu= 13.2%																
下方光束 Fd= 86.8%																
最大取付間隔		A← 水平距離(m) →B 														
A-A 1.30 H																
B-B 1.26 H																
保守率	良 0.86	配光曲線 (cd/1000 lm)														
中 0.81																
否 0.72																
光度 (cd/1000 lm)																
A-0	B-B	C-0	A'-0	C'-0												
0	248	248	248	248												248
10	279	246	267	207												216
20	308	231	281	160												179
30	322	209	286	107												135
40	327	179	278	66												91
50	322	144	263	25												49
60	308	107	238													14
70	281	67	210													
80	243	26	173													
90	207	3	134													
100	157	3	89													
110	107	2	55													
120	69	1	26													
130	35	1	13													
140	17	1	7													
150	7	1	4													
160	4	1	2													
170	4	2	2													
180																

単体照度分布(初期値)



配光曲線
(cd/1000 lm)

