




# 日立照明器具 照明特性

|   |      |  |      |      |      |      |      |      |      |      |      |      |      |      |      |    |
|---|------|--|------|------|------|------|------|------|------|------|------|------|------|------|------|----|
| 名称: 交換形LEDトラフ形<br>CP付   | 反射率  | 天井   | 80%  |      |      | 70%  |      |      |      | 50%  |      |      | 30%  |      |      | 0% |
|   |      | 壁  | 70%  | 50%  | 30%  | 70%  | 50%  | 30%  | 10%  | 50%  | 30%  | 10%  | 50%  | 30%  | 10%  | 0% |
|   |      | 床  | 10%  |      |      |      |      |      |      |      |      |      |      |      |      |    |
| 形式: PC4A1CP   | 室指数  | 固有照明率 S/H=1.0  |      |      |      |      |      |      |      |      |      |      |      |      |      |    |
| ＜備考＞  | 0.6  | 0.57   | 0.45 | 0.37 | 0.55 | 0.44 | 0.36 | 0.31 | 0.42 | 0.36 | 0.31 | 0.41 | 0.35 | 0.31 | 0.28 |    |
|   | 0.8  | 0.66   | 0.54 | 0.46 | 0.64 | 0.53 | 0.46 | 0.40 | 0.52 | 0.45 | 0.40 | 0.50 | 0.44 | 0.39 | 0.37 |    |
| 姿図<br> | 1    | 0.72   | 0.61 | 0.53 | 0.70 | 0.60 | 0.53 | 0.47 | 0.58 | 0.52 | 0.47 | 0.56 | 0.51 | 0.46 | 0.43 |    |
|   | 1.25 | 0.78   | 0.68 | 0.61 | 0.76 | 0.67 | 0.60 | 0.54 | 0.65 | 0.58 | 0.53 | 0.63 | 0.57 | 0.53 | 0.50 |    |
|   | 1.5  | 0.82   | 0.73 | 0.66 | 0.81 | 0.72 | 0.65 | 0.60 | 0.70 | 0.64 | 0.59 | 0.67 | 0.62 | 0.58 | 0.55 |    |
|   | 2    | 0.88   | 0.80 | 0.74 | 0.86 | 0.79 | 0.73 | 0.68 | 0.76 | 0.71 | 0.67 | 0.74 | 0.70 | 0.66 | 0.63 |    |
|   | 2.5  | 0.92   | 0.85 | 0.79 | 0.90 | 0.83 | 0.78 | 0.74 | 0.81 | 0.76 | 0.72 | 0.78 | 0.74 | 0.71 | 0.68 |    |
|   | 3    | 0.94   | 0.88 | 0.83 | 0.92 | 0.86 | 0.82 | 0.78 | 0.84 | 0.80 | 0.76 | 0.81 | 0.77 | 0.74 | 0.71 |    |
|   | 4    | 0.97   | 0.92 | 0.88 | 0.95 | 0.91 | 0.87 | 0.83 | 0.88 | 0.84 | 0.81 | 0.85 | 0.82 | 0.80 | 0.76 |    |
| 光源形式<br>CE404WE-N14A  | 5    | 0.99   | 0.95 | 0.91 | 0.97 | 0.94 | 0.90 | 0.87 | 0.91 | 0.88 | 0.85 | 0.88 | 0.85 | 0.83 | 0.80 |    |
| 器具光束<br>4,350 lm  | 7    | 1.02   | 0.99 | 0.96 | 1.00 | 0.97 | 0.95 | 0.92 | 0.94 | 0.92 | 0.90 | 0.91 | 0.90 | 0.88 | 0.84 |    |
|   | 10   | 1.04   | 1.02 | 1.00 | 1.02 | 1.00 | 0.98 | 0.96 | 0.97 | 0.95 | 0.94 | 0.94 | 0.93 | 0.92 | 0.88 |    |
| 器具効率 Ft= 100%   |      | 単体照度分布(初期値)<br>           |      |      |      |      |      |      |      |      |      |      |      |      |      |    |
| 上方光束 Fu= 3.5%   |      |  |      |      |      |      |      |      |      |      |      |      |      |      |      |    |
| 下方光束 Fd= 96.5%  |      |  |      |      |      |      |      |      |      |      |      |      |      |      |      |    |
| 最大取付間隔  |      | 配光曲線<br>(cd/1000 lm)<br> |      |      |      |      |      |      |      |      |      |      |      |      |      |    |
| A-A   | 1.28 |  |      |      |      |      |      |      |      |      |      |      |      |      |      | H  |
| B-B   | 1.26 |  |      |      |      |      |      |      |      |      |      |      |      |      |      | H  |
| 保守率   | 良    | 0.88   |      |      |      |      |      |      |      |      |      |      |      |      |      |    |
|   | 中    | 0.86   |      |      |      |      |      |      |      |      |      |      |      |      |      |    |
|   | 否    | 0.81   |      |      |      |      |      |      |      |      |      |      |      |      |      |    |
| 光度 (cd/1000 lm)   |      | A-0  | B-B  | C-0  | A'-0 | C'-0 |      |      |      |      |      |      |      |      |      |    |
| 0   | 318  | 318  | 318  |      |      |      |      |      |      |      |      |      |      |      |      |    |
| 10  | 312  | 313  | 313  |      |      |      |      |      |      |      |      |      |      |      |      |    |
| 20  | 296  | 295  | 296  |      |      |      |      |      |      |      |      |      |      |      |      |    |
| 30  | 271  | 268  | 268  |      |      |      |      |      |      |      |      |      |      |      |      |    |
| 40  | 239  | 232  | 235  |      |      |      |      |      |      |      |      |      |      |      |      |    |
| 50  | 197  | 189  | 191  |      |      |      |      |      |      |      |      |      |      |      |      |    |
| 60  | 154  | 136  | 148  |      |      |      |      |      |      |      |      |      |      |      |      |    |
| 70  | 110  | 89   | 102  |      |      |      |      |      |      |      |      |      |      |      |      |    |
| 80  | 69   | 35   | 54   |      |      |      |      |      |      |      |      |      |      |      |      |    |
| 90  | 41   | 5  | 25   |      |      |      |      |      |      |      |      |      |      |      |      |    |
| 100   | 21   | 5  | 12   |      |      |      |      |      |      |      |      |      |      |      |      |    |
| 110   | 13   | 3  | 6    |      |      |      |      |      |      |      |      |      |      |      |      |    |
| 120   | 5    | 2  | 1    |      |      |      |      |      |      |      |      |      |      |      |      |    |
| 130   |      |  |      |      |      |      |      |      |      |      |      |      |      |      |      |    |
| 140   |      |  |      |      |      |      |      |      |      |      |      |      |      |      |      |    |
| 150   |      |  |      |      |      |      |      |      |      |      |      |      |      |      |      |    |
| 160   |      |  |      |      |      |      |      |      |      |      |      |      |      |      |      |    |
| 170   |      |  |      |      |      |      |      |      |      |      |      |      |      |      |      |    |
| 180   |      |  |      |      |      |      |      |      |      |      |      |      |      |      |      |    |