

日立照明器具 照明特性

名称: 交換形LEDトラフ形 CP付	反射率	天井	80%			70%				50%			30%			0%		
		壁	70%	50%	30%	70%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0%		
		床	10%														0%	
形式: PC4A1CP	室指数	固有照明率 S/H=1.0																
<備考>	0.6	0.57	0.45	0.37	0.55	0.44	0.36	0.31	0.42	0.36	0.31	0.41	0.35	0.31	0.28			
	0.8	0.66	0.54	0.46	0.64	0.53	0.46	0.40	0.52	0.45	0.40	0.50	0.44	0.39	0.37			
姿図 	1	0.72	0.61	0.53	0.70	0.60	0.53	0.47	0.58	0.52	0.47	0.56	0.51	0.46	0.43			
	1.25	0.78	0.68	0.61	0.76	0.67	0.60	0.54	0.65	0.58	0.53	0.63	0.57	0.53	0.50			
	1.5	0.82	0.73	0.66	0.81	0.72	0.65	0.60	0.70	0.64	0.59	0.67	0.62	0.58	0.55			
	2	0.88	0.80	0.74	0.86	0.79	0.73	0.68	0.76	0.71	0.67	0.74	0.70	0.66	0.63			
	2.5	0.92	0.85	0.79	0.90	0.83	0.78	0.74	0.81	0.76	0.72	0.78	0.74	0.71	0.68			
	3	0.94	0.88	0.83	0.92	0.86	0.82	0.78	0.84	0.80	0.76	0.81	0.77	0.74	0.71			
光源形式 CE405WWG-C14A	4	0.97	0.92	0.88	0.95	0.91	0.87	0.83	0.88	0.84	0.81	0.85	0.82	0.80	0.76			
	5	0.99	0.95	0.91	0.97	0.94	0.90	0.87	0.91	0.88	0.85	0.88	0.85	0.83	0.80			
器具光束 5,040 lm	7	1.02	0.99	0.96	1.00	0.97	0.95	0.92	0.94	0.92	0.90	0.91	0.90	0.88	0.84			
	10	1.04	1.02	1.00	1.02	1.00	0.98	0.96	0.97	0.95	0.94	0.94	0.93	0.92	0.88			
器具効率 Ft= 100%		単体照度分布(初期値) <div>800 600 400 200</div> <div>3.0 1.5 0.0 1.5 3.0</div> <div>0.0 1.5 3.0</div> <div>A ← 水平距離(m) → B</div> <div>(E) lux</div> <div>0-200 200-400 400-600 600-800 800-1000</div>																
上方光束 Fu= 3.5%																		
下方光束 Fd= 96.5%																		
最大取付間隔		<div>A-A 1.28 H</div> <div>B-B 1.26 H</div> <div>保守率</div> <div>良 0.88</div> <div>中 0.86</div> <div>否 0.81</div>																
A-A 1.28 H																		
B-B 1.26 H																		
保守率																		
良 0.88																		
中 0.86																		
否 0.81																		
光度 (cd/1000 lm)		配光曲線 (cd/1000 lm) <div>180 150 120 90 60 30 0</div> <div>350.0 300.0 250.0 200.0 150.0 100.0 50.0 0.0</div> <div>150 120 90 60 30 0</div> <div>A B C-C'</div>																
A-0	B-B															C-0	A'-0	C'-0
0	318															318	318	
10	312															313	313	
20	296															295	296	
30	271															268	268	
40	239															232	235	
50	197															189	191	
60	154															136	148	
70	110															89	102	
80	69															35	54	
90	41															5	25	
100	21															5	12	
110	13															3	6	
120	5															2	1	
130																		
140																		
150																		
160																		
170																		
180																		