

日立照明器具 照明特性

名称: 人感センサー付 交換形ベース器具 (トラフ形)		反射率	天井	80%			70%			50%			30%			0%
		壁	70%	50%	30%	70%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0%
形式: PC4A1SL		床	10%												0%	
<備考>		固有照明率 S/H=1.0														
		0.6	0.57	0.45	0.37	0.55	0.44	0.36	0.31	0.42	0.36	0.31	0.41	0.35	0.31	0.28
		0.8	0.66	0.54	0.46	0.64	0.53	0.46	0.40	0.52	0.45	0.40	0.50	0.44	0.39	0.37
姿図		1	0.72	0.61	0.53	0.70	0.60	0.53	0.47	0.58	0.52	0.47	0.56	0.51	0.46	0.43
		1.25	0.78	0.68	0.61	0.76	0.67	0.60	0.54	0.65	0.58	0.53	0.63	0.57	0.53	0.50
		1.5	0.82	0.73	0.66	0.81	0.72	0.65	0.60	0.70	0.64	0.59	0.67	0.62	0.58	0.55
		2	0.88	0.80	0.74	0.86	0.79	0.73	0.68	0.76	0.71	0.67	0.74	0.70	0.66	0.63
		2.5	0.92	0.85	0.79	0.90	0.83	0.78	0.74	0.81	0.76	0.72	0.78	0.74	0.71	0.68
		3	0.94	0.88	0.83	0.92	0.86	0.82	0.78	0.84	0.80	0.76	0.81	0.77	0.74	0.71
光源形式		4	0.97	0.92	0.88	0.95	0.91	0.87	0.83	0.88	0.84	0.81	0.85	0.82	0.80	0.76
CE402WWE-X14A		5	0.99	0.95	0.91	0.97	0.94	0.90	0.87	0.91	0.88	0.85	0.88	0.85	0.83	0.80
器具光束		7	1.02	0.99	0.96	1.00	0.97	0.95	0.92	0.94	0.92	0.90	0.91	0.90	0.88	0.84
2,130 lm		10	1.04	1.02	1.00	1.02	1.00	0.98	0.96	0.97	0.95	0.94	0.94	0.93	0.92	0.88
器具効率 Ft= 100%		単体照度分布(初期値)														
上方光束 Fu= 3.5%		3.0														
下方光束 Fd= 96.5%		1.5														
最大取付間隔		0.0														
A-A 1.28 H		800 600 400 200														
B-B 1.26 H		3.0														
保守率	良	単体照度分布(初期値)														
	中	3.0														
	否	1.5														
光度(cd/1000 lm)		0.0														
	A-0	B-B	C-0	A'-0	C'-0	水平距離(m)										
0	318	318	318			A ← → B										
10	312	313	313			3.0										
20	296	295	296			1.5										
30	271	268	268			0.0										
40	239	232	235			800 600 400 200										
50	197	189	191			3.0										
60	154	136	148			1.5										
70	110	89	102			0.0										
80	69	35	54			3.0										
90	41	5	25			1.5										
100	21	5	12			0.0										
110	13	3	6			3.0										
120	5	2	1			1.5										
130						0.0										
140						3.0										
150						1.5										
160						0.0										
170						3.0										
180						1.5										

