

## 日立照明器具 照明特性

名称: 交換形LED笠付形	反射率	天井	80%			70%			50%			30%			0%					
		壁	70%	50%	30%	70%	50%	30%	10%	50%	30%	10%	50%	30%	10%					
		床	10%												0%					
形式: PC4B1		室指数	固有照明率 S/H=1.0																	
<備考>		0.6	0.58	0.46	0.38	0.57	0.46	0.38	0.33	0.44	0.38	0.33	0.43	0.37	0.33	0.31				
		0.8	0.68	0.56	0.49	0.66	0.56	0.48	0.43	0.54	0.47	0.42	0.53	0.47	0.42	0.40				
姿図		1	0.74	0.63	0.56	0.73	0.63	0.55	0.50	0.61	0.55	0.50	0.59	0.54	0.49	0.47				
		1.25	0.80	0.70	0.63	0.78	0.69	0.63	0.57	0.68	0.62	0.57	0.66	0.61	0.56	0.54				
		1.5	0.84	0.76	0.69	0.83	0.75	0.68	0.63	0.73	0.67	0.63	0.71	0.66	0.62	0.60				
		2	0.90	0.83	0.77	0.88	0.82	0.76	0.72	0.80	0.75	0.71	0.78	0.74	0.70	0.67				
		2.5	0.93	0.87	0.82	0.92	0.86	0.81	0.77	0.84	0.80	0.76	0.82	0.78	0.75	0.72				
		3	0.96	0.90	0.86	0.94	0.89	0.85	0.81	0.87	0.83	0.80	0.85	0.81	0.79	0.76				
光源形式		4	0.99	0.94	0.90	0.97	0.93	0.90	0.86	0.91	0.88	0.85	0.89	0.86	0.84	0.81				
CE405WWG-X14A		5	1.01	0.97	0.94	0.99	0.96	0.93	0.90	0.94	0.91	0.89	0.91	0.89	0.87	0.84				
器具光束		7	1.03	1.01	0.98	1.02	0.99	0.97	0.95	0.97	0.95	0.93	0.95	0.93	0.92	0.89				
4,950 lm		10	1.05	1.03	1.02	1.04	1.02	1.00	0.99	1.00	0.98	0.97	0.97	0.96	0.95	0.92				
器具効率 $F_t = 100\%$		単体照度分布(初期値)																		
上方光束 $F_u = 0.5\%$		3.0																		
下方光束 $F_d = 99.5\%$		0.0																		
最大取付間隔		0.0																		
A-A 1.28 H		1.5																		
B-B 1.26 H		0.0																		
保守率		1.5																		
良		3.0																		
中		0.0																		
否		3.0																		
光度 (cd/1000 lm)		0.0																		
A	A-0	B-B	C-0	A'-0	C'-0	水平距離(m)														
0	344	344	344			A←														
10	338	339	337			→B														
20	323	321	321			0.0														
30	293	290	292			1.5														
40	253	249	251			3.0														
50	213	206	210			0.0														
60	157	153	156			1.5														
70	94	95	99			3.0														
80	28	43	41			0.0														
90		5	1			1.5														
100		5	1			3.0														
110		3	1			0.0														
120		2	1			1.5														
130						3.0														
140						0.0														
150						1.5														
160						3.0														
170						0.0														
180						1.5														

