

## 日立照明器具 照明特性

名称: 交換形LED笠付形	反射率	天井	80%			70%			50%			30%			0%			
		壁	70%	50%	30%	70%	50%	30%	10%	50%	30%	10%	50%	30%	10%			
		床	10%												0%			
形式: PC4B1		室指数	固有照明率 S/H=1.0															
<備考>		0.6	0.58	0.46	0.38	0.57	0.46	0.38	0.33	0.44	0.38	0.33	0.43	0.37	0.33	0.31		
		0.8	0.68	0.56	0.49	0.66	0.56	0.48	0.43	0.54	0.47	0.42	0.53	0.47	0.42	0.40		
姿図		1	0.74	0.63	0.56	0.73	0.63	0.55	0.50	0.61	0.55	0.50	0.59	0.54	0.49	0.47		
		1.25	0.80	0.70	0.63	0.78	0.69	0.63	0.57	0.68	0.62	0.57	0.66	0.61	0.56	0.54		
		1.5	0.84	0.76	0.69	0.83	0.75	0.68	0.63	0.73	0.67	0.63	0.71	0.66	0.62	0.60		
		2	0.90	0.83	0.77	0.88	0.82	0.76	0.72	0.80	0.75	0.71	0.78	0.74	0.70	0.67		
		2.5	0.93	0.87	0.82	0.92	0.86	0.81	0.77	0.84	0.80	0.76	0.82	0.78	0.75	0.72		
		3	0.96	0.90	0.86	0.94	0.89	0.85	0.81	0.87	0.83	0.80	0.85	0.81	0.79	0.76		
光源形式		4	0.99	0.94	0.90	0.97	0.93	0.90	0.86	0.91	0.88	0.85	0.89	0.86	0.84	0.81		
CE406WG-X14A		5	1.01	0.97	0.94	0.99	0.96	0.93	0.90	0.94	0.91	0.89	0.91	0.89	0.87	0.84		
器具光束		7	1.03	1.01	0.98	1.02	0.99	0.97	0.95	0.97	0.95	0.93	0.95	0.93	0.92	0.89		
5,780 lm		10	1.05	1.03	1.02	1.04	1.02	1.00	0.99	1.00	0.98	0.97	0.97	0.96	0.95	0.92		
器具効率 Ft= 100%		単体照度分布(初期値)																
上方光束 Fu= 0.5%		3.0																
下方光束 Fd= 99.5%		0.0																
最大取付間隔		0.0																
A-A 1.28 H		1.5																
B-B 1.26 H		0.0																
保守率		1.5																
良		3.0																
中		0.0																
否		3.0																
光度 (cd/1000 lm)		0.0																
A	A-0	B-B	C-0	A'-0	C'-0	水平距離(m)												
0	344	344	344			A← →B												
10	338	339	337			3.0												
20	323	321	321			0.0												
30	293	290	292			1.5												
40	253	249	251			3.0												
50	213	206	210			0.0												
60	157	153	156			1.5												
70	94	95	99			3.0												
80	28	43	41			0.0												
90		5	1			1.5												
100		5	1			3.0												
110		3	1			0.0												
120		2	1			1.5												
130						3.0												
140						0.0												
150						1.5												
160						3.0												
170						0.0												
180						1.5												

