





日立照明器具 照明特性

名称: 交換形LEDトラフ形	反射率	天井	80%			70%				50%			30%			0%															
			70%	50%	30%	70%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0%															
			10%													0%															
形式: PC8A	室指数		固有照明率 S/H=1.0																												
〈備考〉	0.6	0.57	0.45	0.37	0.55	0.44	0.36	0.31	0.42	0.36	0.31	0.41	0.35	0.31	0.28																
	0.8	0.66	0.54	0.46	0.64	0.53	0.46	0.40	0.52	0.45	0.40	0.50	0.44	0.39	0.37																
姿図 	1	0.72	0.61	0.53	0.70	0.60	0.53	0.47	0.58	0.52	0.47	0.56	0.51	0.46	0.43																
	1.25	0.78	0.68	0.61	0.76	0.67	0.60	0.54	0.65	0.58	0.53	0.63	0.57	0.53	0.50																
	1.5	0.82	0.73	0.66	0.81	0.72	0.65	0.60	0.70	0.64	0.59	0.67	0.62	0.58	0.55																
	2	0.88	0.80	0.74	0.86	0.79	0.73	0.68	0.76	0.71	0.67	0.74	0.70	0.66	0.63																
	2.5	0.92	0.85	0.79	0.90	0.83	0.78	0.74	0.81	0.76	0.72	0.78	0.74	0.71	0.68																
	3	0.94	0.88	0.83	0.92	0.86	0.82	0.78	0.84	0.80	0.76	0.81	0.77	0.74	0.71																
	4	0.97	0.92	0.88	0.95	0.91	0.87	0.83	0.88	0.84	0.81	0.85	0.82	0.80	0.76																
光源形式 CE812DE-X24A	5	0.99	0.95	0.91	0.97	0.94	0.90	0.87	0.91	0.88	0.85	0.88	0.85	0.83	0.80																
器具光束 11,410 lm	7	1.02	0.99	0.96	1.00	0.97	0.95	0.92	0.94	0.92	0.90	0.91	0.90	0.88	0.84																
	10	1.04	1.02	1.00	1.02	1.00	0.98	0.96	0.97	0.95	0.94	0.94	0.93	0.92	0.88																
器具効率 Ft= 100%		単体照度分布(初期値) 																													
上方光束 Fu= 3.5%																															
下方光束 Fd= 96.5%																															
最大取付間隔																															
A-A 1.28 H																															
B-B 1.26 H																															
保守率																															
良 0.88																															
中 0.86																															
否 0.81																															
光度 (cd/1000 lm)																															
A-0																															
B-B																															
C-0																															
0	318	318	318																												
10	312	313	313																												
20	296	295	296																												
30	271	268	268																												
40	239	232	235																												
50	197	189	191																												
60	154	136	148																												
70	110	89	102																												
80	69	35	54																												
90	41	5	25																												
100	21	5	12																												
110	13	3	6																												
120	5	2	1																												
130																															
140																															
150																															
160																															
170																															
180																															