



# 日立照明器具 照明特性

名称: 交換形LED逆富士形		天井	80%			70%				50%			30%			0%			
			壁	70%	50%	30%	70%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0%		
																		床	10%
形式: WGN8B1		反射率	固有照明率 S/H=1.0																
<備考> 防湿・防雨形 (オイルミスト対応)		室指数	0.6	0.56	0.44	0.36	0.54	0.43	0.35	0.30	0.41	0.35	0.30	0.40	0.34	0.29	0.27		
		0.8	0.65	0.53	0.45	0.63	0.52	0.45	0.39	0.51	0.44	0.39	0.49	0.43	0.38	0.35			
姿図		1	0.71	0.60	0.52	0.69	0.59	0.52	0.46	0.57	0.50	0.45	0.55	0.49	0.44	0.42			
		1.25	0.77	0.67	0.59	0.75	0.66	0.59	0.53	0.63	0.57	0.52	0.61	0.55	0.51	0.48			
		1.5	0.81	0.72	0.65	0.79	0.71	0.64	0.59	0.68	0.62	0.57	0.66	0.61	0.56	0.53			
		2	0.87	0.79	0.73	0.85	0.78	0.72	0.67	0.75	0.70	0.65	0.72	0.68	0.64	0.60			
		2.5	0.91	0.84	0.78	0.88	0.82	0.77	0.72	0.79	0.74	0.70	0.76	0.72	0.69	0.65			
		3	0.93	0.87	0.82	0.91	0.85	0.80	0.76	0.82	0.78	0.74	0.79	0.75	0.72	0.69			
光源形式 WGE402LE-N14A1		4	0.96	0.91	0.87	0.94	0.89	0.85	0.82	0.86	0.83	0.80	0.83	0.80	0.77	0.74			
		5	0.98	0.94	0.90	0.96	0.92	0.89	0.86	0.89	0.86	0.83	0.86	0.83	0.81	0.77			
器具光束 4,120 lm		7	1.01	0.98	0.95	0.99	0.96	0.93	0.91	0.93	0.90	0.88	0.89	0.88	0.86	0.82			
		10	1.03	1.01	0.99	1.01	0.99	0.97	0.95	0.96	0.94	0.92	0.92	0.91	0.90	0.86			
器具効率 Ft= 100%			単体照度分布(初期値) 																
上方光束 Fu= 5.2%																			
下方光束 Fd= 94.8%																			
最大取付間隔			配光曲線 (cd/1000 lm) 																
A-A 1.28 H																			
B-B 1.26 H																			
保守率	良	0.88																	
	中	0.86																	
	否	0.81																	
光度 (cd/1000 lm)																			
	A-0	B-B	C-0	A'-0	C'-0														
0	303	303	303																
10	297	300	298																
20	283	282	282																
30	260	257	257																
40	230	221	225																
50	193	176	185																
60	160	130	142																
70	119	81	102																
80	83	30	62																
90	54	1	33																
100	33		17																
110	18		7																
120	11		5																
130	6		4																
140	4		3																
150	4		2																
160																			
170																			
180																			