

仕様表 ゆかおき／厨房用てんつり (別表 p.269)

Table with columns for Model, Power, Capacity, Dimensions, Mass, Electrical Characteristics, and Performance. Rows include models like RPV-AP224SHG6, RPV-AP280SHG6, etc.

厨房用てんつり 省エネの達人プレミアム R32

Table for R32 Premium models including RPCK-GP80RGHJ2, RPCK-GP80RGH2, RPCK-GP140RGH2, RPCK-GP160RGHP2.

厨房用てんつり 省エネの達人 R32

Table for standard R32 models including RPCK-GP80RSHJ2, RPCK-GP80RSH2, RPCK-GP140RSH2, RPCK-GP160RSHP2.

厨房用てんつり 省エネの達人プレミアム R410A

Table for R410A Premium models including RPCK-AP80GHJ7, RPCK-AP80GH7, RPCK-AP140GH7, RPCK-AP160GHP7, RPCK-AP280GHP7, RPCK-AP224GHG7, RPCK-AP335GHW7.

厨房用てんつり 省エネの達人 R410A

Table for standard R410A models including RPCK-AP280SHP7, RPCK-AP224SHG7, RPCK-AP335SHW7.

IPコード：室内…X0、室外…X4 設計圧力：4.15MPa 仕様値は、JIS B 8616:2015による

2015年3月のJIS改正にともない、通年エネルギー消費効率はAPF2015、運転音は音響パワーレベルを記載しています。

- (注)・能力の()内はインバーターによる可変範囲を示します。・厨房用てんつりは、冷房負荷の高い場所に設置しますでツイン・トリプル・フォーでご利用の場合には、各エアコンの吸い込み空気温度が均一な場所でご使用ください。

- ・省エネの達人プレミアム(R410A)・省エネの達人(R410A)個別運転トリプル・フォー機、寒さ知らず個別運転トリプル・フォー機、省エネの達人プレミアム(R410A)・省エネの達人(R410A)・寒さ知らず同時運転フォー機はe-LINE接続はできません。

注)「ゆかおき(224・280型)」はH急の設定ができません。 ※配管長が70m以上の場合は、液配管をφ12.7にサイズアップしてください。

- ・電気特性の運転電流欄の「冷房」または「暖房」の電流値が20Aを超える空調機は、「高圧又は特別高圧」で受電する需要家の高調波抑制対策ガイドライン」対象機器となります。回路種別番号、換算係数は機種により異なりますので営業窓口までお問い合わせください。

ゆかおき／厨房用てんつり仕様表

ゆかおき／厨房用てんつり仕様表